SATCO NUVO

Project Name

Prepared By



SATCO S23115

130W/LED/HID-HB/5K/120-277V

Notes

| Status | Discontinued |
|-------------------------|---|
| Substitute | S33115 |
| Watts | 130W |
| Incandescent Equivalent | 250W |
| HID Equivalent | 400W |
| Volts | 120V-277V |
| Shape | HB77 |
| Base | Mogul Extended |
| ANSI Base | EX39 |
| Finish | Translucent White |
| CCT (Kelvin) | 5000K |
| Temperature | Natural Light |
| CRI | 80+ |
| Lumens | 16300L |
| Beam Spread | 115 |
| Dimmable | Yes-Dimmable |
| Hours Rated | 35000 |
| Product Category | Hi-Bay |
| Technology | LED |
| Min Compartment Size | Length: 16.5 in. Width: 16.5 in. Height: 13 in. |
| Ballasting Requirements | Ballast Bypass |

| Electrical | | |
|-----------------------|---|--|
| Operating Frequency | 50-60Hz | |
| Candlepower | 5000 | |
| Dimming Type | Step Dimming | |
| Dimming Note | Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch | |
| Power Factor | 0.99/0.95 | |
| Operating Position | Universal | |
| Surge Protection | Built-in surge protection - 6KV | |
| Operating Temperature | -40C (-40F) to +60C (+140F) | |

| Physical | |
|---------------|---------|
| MOL | 12.4 |
| MOD | 9.65 |
| Lens Material | Plastic |
| Housing Color | White |
| Weight (lb.) | 2.98 |

| Additional Information | | |
|----------------------------|--|--|
| Rated For Enclosed Fixture | Yes | |
| Specification Note | Fixture has built-in dimming control feature | |
| Installation Notes | Not for use in vapor tight fixtures. | |
| Warranty | 5-Years | |

| Compliance | | |
|----------------------|---------------------------------------|--|
| Safety Listing | cULus - Classified; cULus - Certified | |
| Location Rating | Damp | |
| DLC Approved | No | |
| California Status | Lawful for sale in California | |
| Title 20 / 24 Status | Lawful for sale | |
| RoHS Compliant | Yes | |
| FCC Compliant | Yes | |
| SDS Sheet | LED_Lamp | |