

Project Name

Location

Prepared By



SATCO S23115

130W/LED/HID-HB/5K/120-277V

Notes

(www) 18-17-0025 01/20/07

General

Status	Discontinued
Substitute	S33115
Watts	130W
Incandescent Equivalent	250W
HID Equivalent	400W
Volts	120V-277V
Shape	HB77
Base	Mogul Extended
ANSI Base	EX39
Finish	Translucent White
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	16300L
Beam Spread	115
Dimmable	Yes-Dimmable
Hours Rated	35000
Product Category	Hi-Bay
Technology	LED
Min Compartment Size	Length: 16.5 in. Width: 16.5 in. Height: 13 in.
Ballasting Requirements	Ballast Bypass

Electrical

Operating Frequency	50-60Hz
Candlepower	5000
Dimming Type	Step Dimming
Dimming Note	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch
Power Factor	0.99/0.95
Operating Position	Universal
Surge Protection	Built-in surge protection - 6KV
Operating Temperature	-40C (-40F) to +60C (+140F)

Physical

MOL	12.4
MOD	9.65
Lens Material	Plastic
Housing Color	White
Weight (lb.)	2.98

Additional Information

Rated For Enclosed Fixture	Yes
Specification Note	Fixture has built-in dimming control feature
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years

Compliance

Safety Listing	cULus - Classified; cULus - Certified
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp