SATCO NUVO

Project Name

ocation

Prepared By



SATCO S23136

270W/LED/CCT/100-277V/EX39

Notes

ww1 10-27-2025 05:20:0

Surge Protection

Operating Temperature

THD

General	
Status	Active
Watts	270W/200W/135W
HID Equivalent	600W
Volts	120V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	White
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Soft White to Natural Light
CRI	80+
Lumens	45330L/34581L/24450L
Beam Spread	280
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Min Compartment Size	Length: 18.50 in. Width:14.96 in. Height: 14.96 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	60Hz
Dimming Type	Step Dimming
Dimming Note	Only dimmable through wattage selection switch on lamp
Power Factor	0.99
Operating Position	Universal

Physical	
MOL	12.3
MOD	5.6
Lens Finish	Clear
Lens Material	Polycarbonate (PC)
Housing Color	White
Weight (lb.)	3.56

<20%

Built-in surge protection - 6KV

-40C (-40F) to +50C (+122F)

Additional Information		
Additional Info	Decibels: 47.5dB(A)	
Rated For Enclosed Fixture	Yes	
IP Rating	IP54	
Installation Notes	Not for use in vapor tight fixtures.	
Warranty	5-Years	

Compliance	
Safety Listing	cULus - Listed; cULus - Classified
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-V5JZ45
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

