

Project Name

Location

Prepared By



## SATCO S23141

45W/LED/CCT/100-277V/EX39

### Notes

1www|10-27-2025 05:20:07

### General

Status	Active
Watts	45W/36W/27W
Incandescent Equivalent	125W
HID Equivalent	175W/150W/125W
Volts	120V-277V
Shape	Corn cob
Base	Mogul Extended
ANSI Base	EX39
Finish	White
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
CRI	80+
Lumens	6300L/5040L/3780L
Beam Spread	300
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Corn cob
Technology	LED
Ballasting Requirements	Ballast Bypass

### Electrical

Operating Frequency	50/60Hz
Dimming Type	Step Dimming
Dimming Note	Only dimmable through wattage selection switch on lamp
Power Factor	>0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 4KV
THD	16.30%
Operating Temperature	-40C (-40F) to +60C (+140F)

### Physical

MOL	9.69
MOD	3.35
Lens Material	Plastic
Housing Color	Dark Gray
Weight (lb.)	1.76

### Additional Information

Additional Info	Safety cable provided with S23143, S23144, S23145 ONLY and is required upon installation of these high bay, base-up applications. (Please See Instructions)
Rated For Enclosed Fixture	Yes
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years

### Compliance

Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-086UBA
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp