SATCO NUVO

Project Name

ocation Prepared By



Notes

vww1 10-27-2025 05:20:

General	
Status	Active
Watts	80W/63W/54W
Incandescent Equivalent	150W-250W
HID Equivalent	320W/250W/200W
Volts	120V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	White
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
CRI	80+
Lumens	11200L/8820L/7560L
Beam Spread	300
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Corncob
Technology	LED
Min Compartment Size	Length: 9.85 in. Width: 9.85 in. Height: 10.95 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Francisco	E0/60H-

Operating Frequency	50/60Hz
Dimming Type	Step Dimming
Dimming Note	Only dimmable through wattage selection switch on lamp
Power Factor	>0.9
Operating Position	Base Up or Down
Surge Protection	Built-in surge protection - 4KV
THD	12.30%
Operating Temperature	-40C (-40F) to +60C (+140F)

Physical	
MOL	9.96
MOD	5.11
Lens Material	Plastic
Housing Color	Dark Gray
Weight (lb.)	2.68

Additional Information	
Additional Info	Safety cable provided with S23143, S23144, S23145 ONLY and is required upon installation of these high bay, base-up applications. (Please See Instructions)
Rated For Enclosed Fixture	Yes
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-7YQW1Z
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

