SATCO NUVO

Project Name

ocation Prepared By



SATCO S23150

63W/LED/CCT/100-277V/EX39

Notes

General	
Status	Active
Watts	63W/54W/45W
Incandescent Equivalent	150W-250W
HID Equivalent	250W/200W/175W
Volts	120V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	White
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
CRI	80+
Lumens	8820L/7560L/6300L
Beam Spread	300
Hours Rated	50000
Product Category	Corncob
Technology	LED
Min Compartment Size	Length: 7.88 in. Width: 7.88 in.
Ballasting Requirements	Ballast Bypass
Electrical	

Electrical		
Operating Frequency	50/60Hz	
Power Factor	>0.9	
Operating Position	Universal	
Surge Protection	Built-in surge protection - 4KV	
THD	14.10%	
Operating Temperature	-40C (-40F) to +60C (+140F)	

Physical	
MOL	10.28
MOD	3.35
Lens Material	Plastic
Housing Color	Dark Gray
Weight (lb.)	1.8

Additional Information	
Additional Info	Safety cable provided with S23143, S23144, S23145 ONLY and is required upon installation of these high bay, base-up applications. (Please See Instructions)
Rated For Enclosed Fixture	Yes
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-ZHMICR
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

