

Project Name

Location

Prepared By



## SATCO S23151

27W/LED/CCT/100-277V/EX39

### Notes

(revised) 07-09-2023 00:10:01

### General

Status	Active
Watts	27W/22W/18W
Incandescent Equivalent	100W
HID Equivalent	125W/100W/75W
Volts	120V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	White
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
CRI	80+
Lumens	3780L/3080L/2520L
Beam Spread	360
Hours Rated	50000
Product Category	Corncob
Technology	LED
Ballasting Requirements	Ballast Bypass

### Electrical

Operating Frequency	50/60Hz
Dimming Type	Step Dimming
Power Factor	>0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 4KV
THD	15.50%
Operating Temperature	-30C (-22F) to +45C (+113F)

### Physical

MOL	7.48
MOD	2.32
Lens Material	Plastic
Housing Color	Dark Gray
Weight (lb.)	0.75

### Additional Information

Additional Info	Safety cable provided with S23143, S23144, S23145 ONLY and is required upon installation of these high bay, base-up applications. (Please See Instructions)
Rated For Enclosed Fixture	Yes
IP Rating	IP64
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years

### Compliance

Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-HJ4T6Y
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp