

Project Name

Location

Prepared By



SATCO S23152

36W/LED/CCT/100-277V/EX39

Notes

1www|10-27-2025 05:20:50

General

Status	Active
Watts	36W/27W/18W
Incandescent Equivalent	125W
HID Equivalent	150W/125W/75W
Volts	120V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	White
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
CRI	80+
Lumens	5040L/3780L/2520L
Beam Spread	360
Hours Rated	50000
Product Category	Corncob
Technology	LED
Ballasting Requirements	Ballast Bypass

Electrical

Operating Frequency	50/60Hz
Power Factor	>0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 4KV
THD	14.20%
Operating Temperature	-30C (-22F) to +45C (+113F)

Physical

MOL	8.5
MOD	3.35
Lens Material	Plastic
Housing Color	Dark Gray
Weight (lb.)	1.47

Additional Information

Additional Info	Safety cable provided with S23143, S23144, S23145 ONLY and is required upon installation of these high bay, base-up applications. (Please See Instructions)
Rated For Enclosed Fixture	Yes
IP Rating	IP64
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years

Compliance

Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-6CIPQ4
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp