SATCO NUVO

Project Name

ocation Prepared By



SATCO S23163

45W/LED/CCT/277-480V/E26

Notes

| Status | Active |
|-------------------------|---------------------------|
| Watts | 45W |
| Incandescent Equivalent | 125W |
| HID Equivalent | 200W |
| Volts | 277V-480V |
| Shape | Corncob |
| Base | Medium |
| ANSI Base | E26 |
| Finish | White |
| CCT (Kelvin) | 3000K/4000K/5000K |
| Temperature | Warm to Cool White |
| CRI | 80+ |
| Lumens | 5850L/6300L/6075L |
| Beam Spread | 300 |
| Dimmable | Yes-Dimmable Yes-Dimmable |
| Hours Rated | 50000 |
| Product Category | Corncob |
| Technology | LED |
| Ballasting Requirements | Ballast Bypass |

| Electrical | |
|-----------------------|---------------------------------|
| Operating Frequency | 50/60Hz |
| Dimming Type | Smart-Starfish App only |
| Dimming Note | Only Dimmable Via Sensor Port |
| Power Factor | 0.9 |
| Operating Position | Universal |
| Surge Protection | Built-in surge protection - 4KV |
| Operating Temperature | -30C (-22F) to +45C (+113F) |

| Physical | |
|---------------------|-----------|
| MOL | 8.91 |
| MOD | 3.35 |
| Lens Finish | Clear |
| Lens Material | Plastic |
| Housing Color | Dark Gray |
| Photocell or Sensor | Optional |
| Weight (lb.) | 1.58 |

| Additional Information | |
|----------------------------|--------------------------------------|
| Rated For Enclosed Fixture | Yes |
| IP Rating | IP64 |
| Installation Notes | Not for use in vapor tight fixtures. |
| Warranty | 5-Years |

| Compliance | |
|----------------------|--|
| Safety Listing | cUL - Certified; cUL - Classified; cRUus - Recognized Component |
| Location Rating | Damp |
| DLC Approved | No |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| SDS Sheet | LED_Lamp |