SATCO NUVO

Project Name

Location

Prepared By



SATCO S23165

45W/LED/CCT/277-480V/EX39

Notes

3.04.45.0004.00.40

Energy Star

| General | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General | |
| Status | Active |
| Watts | 45W |
| Incandescent Equivalent | 125W |
| HID Equivalent | 200W |
| Volts | 277V-480V |
| Shape | Corncob |
| Base | Mogul Extended |
| ANSI Base | EX39 |
| Finish | White |
| CCT (Kelvin) | 3000K/4000K/5000K |
| Temperature | Warm to Cool White |
| CRI | 80 |
| Lumens | 5850L/6300L/6075L |
| Beam Spread | 300 |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Lamp Type | Corncob |
| Technology | LED |
| Min Compartment Size | Length: 10.55 in. Width: 8.00 in. Height: 8.00 in. |
| Ballasting Requirements | Ballast Bypass |
| Electrical | |
| Operating Frequency | 50/60Hz |
| Dimming Type | Smart-Starfish App through Wifi Module only |
| | |
| Dimming Note | Only dimmable via WiFi Module 80- 954 (available for purchase) and via the Starfish App |
| Dimming Note Power Factor | 954 (available for purchase) and |
| | 954 (available for purchase) and via the Starfish App |
| Power Factor | 954 (available for purchase) and via the Starfish App |
| Power Factor Operating Position | 954 (available for purchase) and via the Starfish App 0.9 Universal |
| Power Factor Operating Position Surge Protection | 954 (available for purchase) and via the Starfish App 0.9 Universal Built-in surge protection - 4KV |
| Power Factor Operating Position Surge Protection THD | 954 (available for purchase) and via the Starfish App 0.9 Universal Built-in surge protection - 4KV 8.80% |
| Power Factor Operating Position Surge Protection THD Operating Temperature Physical | 954 (available for purchase) and via the Starfish App 0.9 Universal Built-in surge protection - 4KV 8.80% -30C (-22F) to +45C (+113F) |
| Power Factor Operating Position Surge Protection THD Operating Temperature Physical MOL | 954 (available for purchase) and via the Starfish App 0.9 Universal Built-in surge protection - 4KV 8.80% -30C (-22F) to +45C (+113F) 9.53 |
| Power Factor Operating Position Surge Protection THD Operating Temperature Physical MOL MOD | 954 (available for purchase) and via the Starfish App 0.9 Universal Built-in surge protection - 4KV 8.80% -30C (-22F) to +45C (+113F) 9.53 3.35 |
| Power Factor Operating Position Surge Protection THD Operating Temperature Physical MOL MOD Lens Finish | 954 (available for purchase) and via the Starfish App 0.9 Universal Built-in surge protection - 4KV 8.80% -30C (-22F) to +45C (+113F) 9.53 3.35 Clear |
| Power Factor Operating Position Surge Protection THD Operating Temperature Physical MOL MOD Lens Finish Lens Material | 954 (available for purchase) and via the Starfish App 0.9 Universal Built-in surge protection - 4KV 8.80% -30C (-22F) to +45C (+113F) 9.53 3.35 Clear Plastic |
| Power Factor Operating Position Surge Protection THD Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color | 954 (available for purchase) and via the Starfish App 0.9 Universal Built-in surge protection - 4KV 8.80% -30C (-22F) to +45C (+113F) 9.53 3.35 Clear Plastic Dark Gray |
| Power Factor Operating Position Surge Protection THD Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Photocell or Sensor | 954 (available for purchase) and via the Starfish App 0.9 Universal Built-in surge protection - 4KV 8.80% -30C (-22F) to +45C (+113F) 9.53 3.35 Clear Plastic Dark Gray Optional |
| Power Factor Operating Position Surge Protection THD Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Photocell or Sensor Weight (lb.) | 954 (available for purchase) and via the Starfish App 0.9 Universal Built-in surge protection - 4KV 8.80% -30C (-22F) to +45C (+113F) 9.53 3.35 Clear Plastic Dark Gray |
| Power Factor Operating Position Surge Protection THD Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Photocell or Sensor | 954 (available for purchase) and via the Starfish App 0.9 Universal Built-in surge protection - 4KV 8.80% -30C (-22F) to +45C (+113F) 9.53 3.35 Clear Plastic Dark Gray Optional |
| Power Factor Operating Position Surge Protection THD Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Photocell or Sensor Weight (lb.) | 954 (available for purchase) and via the Starfish App 0.9 Universal Built-in surge protection - 4KV 8.80% -30C (-22F) to +45C (+113F) 9.53 3.35 Clear Plastic Dark Gray Optional |
| Power Factor Operating Position Surge Protection THD Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Photocell or Sensor Weight (lb.) Additional Information | 954 (available for purchase) and via the Starfish App 0.9 Universal Built-in surge protection - 4KV 8.80% -30C (-22F) to +45C (+113F) 9.53 3.35 Clear Plastic Dark Gray Optional 1.6 |
| Power Factor Operating Position Surge Protection THD Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Photocell or Sensor Weight (lb.) Additional Information Rated For Enclosed Fixture | 954 (available for purchase) and via the Starfish App 0.9 Universal Built-in surge protection - 4KV 8.80% -30C (-22F) to +45C (+113F) 9.53 3.35 Clear Plastic Dark Gray Optional 1.6 |
| Power Factor Operating Position Surge Protection THD Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Photocell or Sensor Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating | 954 (available for purchase) and via the Starfish App 0.9 Universal Built-in surge protection - 4KV 8.80% -30C (-22F) to +45C (+113F) 9.53 3.35 Clear Plastic Dark Gray Optional 1.6 Yes IP64 |
| Power Factor Operating Position Surge Protection THD Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Photocell or Sensor Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Warranty | 954 (available for purchase) and via the Starfish App 0.9 Universal Built-in surge protection - 4KV 8.80% -30C (-22F) to +45C (+113F) 9.53 3.35 Clear Plastic Dark Gray Optional 1.6 Yes IP64 |
| Power Factor Operating Position Surge Protection THD Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Photocell or Sensor Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance | 954 (available for purchase) and via the Starfish App 0.9 Universal Built-in surge protection - 4KV 8.80% -30C (-22F) to +45C (+113F) 9.53 3.35 Clear Plastic Dark Gray Optional 1.6 Yes IP64 5 Year Limited - Hi-Pro |

No

| DLC Approved | Yes |
|------------------------|-------------------------------|
| DLC ID | S-PBFMTJ |
| CA T20 / T24 Rationale | Exempt - Base Not Regulated |
| NSF Approved | No |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| SDS Sheet | LED_Lamp |

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



