SATCO NUVO

Project Name

ocation Prepared By



Notes

w1 07-16-2025 01:54:1

General	
Status	Active
Watts	3.5W
Incandescent Equivalent	40W
Volts	120V
Shape	B11
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	3000K
Temperature	Soft White
CRI	90+
Lumens	300L
Beam Spread	275
Dimmable	Yes-Dimmable
Hours Rated	25000
Product Category	Candle
Technology	LED
Smart Product Info	
IOT Enabled	No
Integrated Camera	No
Flactuical	
Electrical	
Operating Frequency	60Hz
	60Hz 0.92
Operating Frequency	
Operating Frequency Power Factor	0.92
Operating Frequency Power Factor Operating Position	0.92 Universal
Operating Frequency Power Factor Operating Position Operating Temperature Physical	0.92 Universal -25C (-13F) to +45C (+113F)
Operating Frequency Power Factor Operating Position Operating Temperature	0.92 Universal
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD	0.92 Universal -25C (-13F) to +45C (+113F)
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL	0.92 Universal -25C (-13F) to +45C (+113F) 3.78 1.38
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.)	0.92 Universal -25C (-13F) to +45C (+113F) 3.78 1.38 White
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information	0.92 Universal -25C (-13F) to +45C (+113F) 3.78 1.38 White 0.07
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	0.92 Universal -25C (-13F) to +45C (+113F) 3.78 1.38 White 0.07 Yes
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	0.92 Universal -25C (-13F) to +45C (+113F) 3.78 1.38 White 0.07
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	0.92 Universal -25C (-13F) to +45C (+113F) 3.78 1.38 White 0.07 Yes 5-Years
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	0.92 Universal -25C (-13F) to +45C (+113F) 3.78 1.38 White 0.07 Yes 5-Years CULus - Certified; cULus - Listed
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	0.92 Universal -25C (-13F) to +45C (+113F) 3.78 1.38 White 0.07 Yes 5-Years CULus - Certified; cULus - Listed Damp
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status	0.92 Universal -25C (-13F) to +45C (+113F) 3.78 1.38 White 0.07 Yes 5-Years CULus - Certified; cULus - Listed Damp Lawful for sale in California
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status	0.92 Universal -25C (-13F) to +45C (+113F) 3.78 1.38 White 0.07 Yes 5-Years CULus - Certified; cULus - Listed Damp Lawful for sale in California California T24 Listed
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status	Universal -25C (-13F) to +45C (+113F) 3.78 1.38 White 0.07 Yes 5-Years CULus - Certified; cULus - Listed Damp Lawful for sale in California California T24 Listed Lawful for sale
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status	0.92 Universal -25C (-13F) to +45C (+113F) 3.78 1.38 White 0.07 Yes 5-Years CULus - Certified; cULus - Listed Damp Lawful for sale in California California T24 Listed Lawful for sale Lawful for sale
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status	0.92 Universal -25C (-13F) to +45C (+113F) 3.78 1.38 White 0.07 Yes 5-Years CULus - Certified; cULus - Listed Damp Lawful for sale in California California T24 Listed Lawful for sale Lawful for sale Lawful for sale
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status	0.92 Universal -25C (-13F) to +45C (+113F) 3.78 1.38 White 0.07 Yes 5-Years CULus - Certified; cULus - Listed Damp Lawful for sale in California California T24 Listed Lawful for sale Lawful for sale

Yes

Yes

LED_Lamp

RoHS Compliant

FCC Compliant

SDS Sheet