

Project Name

ocation Prepared By



Notes

1 07-02-2025 00:52

Status	Active	
Watts	13W	
Incandescent Equivalent	50W	
Fluorescent Equivalent	28W	
Volts	120V-277V	
Ballast Type	Туре В	
Shape	T5	
Base	Miniature Bi Pin	
ANSI Base	G5	
Nominal Length	48	
Finish	Frost	
CCT (Kelvin)	5000K	
Temperature	Natural Light	
CRI	80+	
Lumens	1700L	
Beam Spread	240	
Hours Rated	50000	
Product Category	Linear	
Technology	LED	

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-25C (-13F) to +45C (+113F)

Physical	
MOL	46
MOD	0.83
Material	Glass
Lens Finish	Frost
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.37

Additional Information	
Shatter-Proof Type	PET Coated
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Safety Listing	cULus - Classified; cULus - Certified; ETLus - Sanitation Recognized Component
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLJ1EPDXDBTD
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	 LED_Lamp