

Project Name

Location

Prepared By



# SATCO S28928

20W/LED/WP/CCT/E26/100-277V

## Notes

(www) 03-31-2023 09:30:09

### General

Status	Active
Watts	5W/10W/20W
Incandescent Equivalent	25W/40W/60W
HID Equivalent	100W
Volts	120V-277V
Shape	Corncob
Base	Medium
ANSI Base	E26
Finish	White
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
CRI	80+
Lumens	850L/1500L/3000L
Beam Spread	180
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Corncob
Technology	LED
Min Compartment Size	Length: 8 in. Width: 8 in. Height: 11 in.
Ballasting Requirements	Ballast Bypass

### Electrical

Operating Frequency	50-60Hz
Dimming Note	Dimmable only via the wattage/lumen selectable dial included on lamp
Power Factor	>0.9
Operating Position	Horizontal
Surge Protection	Built-in surge protection - 4KV
Operating Temperature	-30C (-22F) to +45C (+113F)

### Physical

MOL	5.43
MOD	3.62
Lens Material	Plastic
Housing Color	White
Weight (lb.)	1

### Additional Information

Rated For Enclosed Fixture	Yes
IP Rating	IP64
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5 Year Limited - Hi-Pro

### Compliance

Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	No
California Status	Non-Compliant
Title 20 / 24 Status	Non-Compliant
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp