SATCO NUVO

Project Name

Location

Prepared By



Notes

www] 01-15-2024 02:40:

Title 20 / 24 Status

General	
Status	Active
Watts	5W/10W/20W
Incandescent Equivalent	25W/40W/60W
HID Equivalent	100W
Volts	100V-277V
Shape	Corncob
Base	Medium
ANSI Base	E26
Finish	White
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
CRI	80
Lumens	850L/1500L/3000L
Beam Spread	180
Dimmable	Yes-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 8 in. Width: 8 in. Height: 11 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	50-60Hz
	D' 11 1 1 1 1
Dimming Note	Dimmable only via the wattage/lumen selectable dial included on lamp
Dimming Note Power Factor	wattage/lumen selectable dial
	wattage/lumen selectable dial included on lamp
Power Factor	wattage/lumen selectable dial included on lamp >0.9
Power Factor Operating Position	wattage/lumen selectable dial included on lamp >0.9 Horizontal
Power Factor Operating Position Surge Protection Operating Temperature	wattage/lumen selectable dial included on lamp >0.9 Horizontal Built-in surge protection - 4KV
Power Factor Operating Position Surge Protection	wattage/lumen selectable dial included on lamp >0.9 Horizontal Built-in surge protection - 4KV
Power Factor Operating Position Surge Protection Operating Temperature	wattage/lumen selectable dial included on lamp >0.9 Horizontal Built-in surge protection - 4KV
Power Factor Operating Position Surge Protection Operating Temperature Physical	wattage/lumen selectable dial included on lamp >0.9 Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F)
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material	wattage/lumen selectable dial included on lamp >0.9 Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 5.43 3.62 Plastic
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD	wattage/lumen selectable dial included on lamp >0.9 Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 5.43 3.62
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material	wattage/lumen selectable dial included on lamp >0.9 Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 5.43 3.62 Plastic
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color	wattage/lumen selectable dial included on lamp >0.9 Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 5.43 3.62 Plastic White
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.)	wattage/lumen selectable dial included on lamp >0.9 Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 5.43 3.62 Plastic White
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information	wattage/lumen selectable dial included on lamp >0.9 Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 5.43 3.62 Plastic White 1
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	wattage/lumen selectable dial included on lamp >0.9 Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 5.43 3.62 Plastic White 1
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating	wattage/lumen selectable dial included on lamp >0.9 Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 5.43 3.62 Plastic White 1 Yes IP64
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Warranty	wattage/lumen selectable dial included on lamp >0.9 Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 5.43 3.62 Plastic White 1 Yes IP64
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance	wattage/lumen selectable dial included on lamp >0.9 Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 5.43 3.62 Plastic White 1 Yes IP64 5 Year Limited - Hi-Pro
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing	wattage/lumen selectable dial included on lamp >0.9 Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 5.43 3.62 Plastic White 1 Yes IP64 5 Year Limited - Hi-Pro
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating	wattage/lumen selectable dial included on lamp >0.9 Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 5.43 3.62 Plastic White 1 Yes IP64 5 Year Limited - Hi-Pro CULus - Listed Damp
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating Energy Star	wattage/lumen selectable dial included on lamp >0.9 Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 5.43 3.62 Plastic White 1 Yes IP64 5 Year Limited - Hi-Pro CULus - Listed Damp No
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved	wattage/lumen selectable dial included on lamp >0.9 Horizontal Built-in surge protection - 4KV -30C (-22F) to +45C (+113F) 5.43 3.62 Plastic White 1 Yes IP64 5 Year Limited - Hi-Pro CULus - Listed Damp No No

Lawful for sale

RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



