

Project Name

Location

Prepared By



SATCO S28929

40W/LED/WP/CCT/E26/100-277V

Notes

[\[www\] 03-28-2023 09:13:09](#)

General

Status	Active
Watts	20W/30W/40W
Incandescent Equivalent	100W
HID Equivalent	175W
Volts	120V-277V
Shape	Corn-cob
Base	Medium
ANSI Base	E26
Finish	White
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
CRI	80+
Lumens	3200L/4700L/6000L
Beam Spread	180
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Corn-cob
Technology	LED
Min Compartment Size	Length: 8 in. Width: 8 in. Height: 11 in.
Ballasting Requirements	Ballast Bypass

Electrical

Operating Frequency	50-60Hz
Dimming Note	Dimmable only via the wattage/lumen selectable dial included on lamp
Power Factor	>0.9
Operating Position	Horizontal
Surge Protection	Built-in surge protection - 4KV
Operating Temperature	-30C (-22F) to +45C (+113F)

Physical

MOL	7.8
MOD	3.62
Lens Material	Plastic
Housing Color	White
Weight (lb.)	1.65

Additional Information

Rated For Enclosed Fixture	Yes
IP Rating	IP64
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5 Year Limited - Hi-Pro

Compliance

Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp