SATCO NUVO

Project Name

Location Prepared By



SATCO S29671

22W/LED/HID/27K/100-277V/E26

Notes

3.04.45.0004.00.40

General	
Status	Discontinued
Substitute	S49671
Watts	22W
Incandescent Equivalent	150W
Fluorescent Equivalent	40W
HID Equivalent	100W
Volts	100V-277V
Shape	Corncob
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	80+
Lumens	2680L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Teermology	Length: 8.5 in. Width: 6 in. Depth:
Min Compartment Size	6 in.
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	
Working Voltage	AC 90-305V
Working Voltage Operating Frequency	AC 90-305V 50/60Hz
Operating Frequency	50/60Hz
Operating Frequency Operating Position Operating Temperature	50/60Hz Universal
Operating Frequency Operating Position Operating Temperature Physical	50/60Hz Universal -20C (-4F) to +40C (+104F)
Operating Frequency Operating Position Operating Temperature Physical MOL	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56
Operating Frequency Operating Position Operating Temperature Physical MOL MOD	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56 2.75
Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56 2.75 Clear
Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56 2.75 Clear White/Grey
Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56 2.75 Clear
Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56 2.75 Clear White/Grey
Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.)	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56 2.75 Clear White/Grey
Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56 2.75 Clear White/Grey 0.96
Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56 2.75 Clear White/Grey 0.96
Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56 2.75 Clear White/Grey 0.96 Yes IP65
Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Warranty	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56 2.75 Clear White/Grey 0.96 Yes IP65
Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56 2.75 Clear White/Grey 0.96 Yes IP65 5 Year Limited - Hi-Pro
Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56 2.75 Clear White/Grey 0.96 Yes IP65 5 Year Limited - Hi-Pro
Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating Energy Star	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56 2.75 Clear White/Grey 0.96 Yes IP65 5 Year Limited - Hi-Pro cULus - Listed Damp
Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56 2.75 Clear White/Grey 0.96 Yes IP65 5 Year Limited - Hi-Pro CULus - Listed Damp No No
Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56 2.75 Clear White/Grey 0.96 Yes IP65 5 Year Limited - Hi-Pro cULus - Listed Damp No
Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56 2.75 Clear White/Grey 0.96 Yes IP65 5 Year Limited - Hi-Pro cULus - Listed Damp No No No Exempt - >2600 Lumens
Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale California Status Title 20 / 24 Status	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56 2.75 Clear White/Grey 0.96 Yes IP65 5 Year Limited - Hi-Pro CULus - Listed Damp No No Exempt - >2600 Lumens Lawful for sale Lawful for sale
Operating Frequency Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale California Status	50/60Hz Universal -20C (-4F) to +40C (+104F) 7.56 2.75 Clear White/Grey 0.96 Yes IP65 5 Year Limited - Hi-Pro cULus - Listed Damp No No No Exempt - >2600 Lumens Lawful for sale in California

Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



