## SATCO NUVO

Project Name

Location

Prepared By



## Notes

General	
Status	Discontinued
Substitute	S49673
Watts	45W
Incandescent Equivalent	300W
Fluorescent Equivalent	65W
HID Equivalent	175W
Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	5850L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 17.3 in. Width: 9.25 in. Depth: 9.25 in.
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	
Mandan a Val	A O OO OOFW
Working Voltage	ΔC: Un=305V
Operating Frequency	AC 90-305V 50/60Hz
Operating Frequency	50/60Hz
Operating Frequency Power Factor	50/60Hz 0.9
Operating Frequency Power Factor Operating Position	50/60Hz 0.9 Base Up or Down
Operating Frequency Power Factor	50/60Hz 0.9
Operating Frequency Power Factor Operating Position Operating Temperature	50/60Hz 0.9 Base Up or Down
Operating Frequency Power Factor Operating Position Operating Temperature Physical	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F)
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F)
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F)  10.75 3.69 Clear
Operating Frequency Power Factor Operating Position Operating Temperature  Physical MOL MOD Lens Finish Housing Color	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F)  10.75 3.69
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish	50/60Hz 0.9 Base Up or Down -20C (-4F) to +40C (+104F)  10.75 3.69 Clear White/Grey
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Lens Finish Housing Color  Weight (lb.)  Additional Information	50/60Hz  0.9  Base Up or Down -20C (-4F) to +40C (+104F)  10.75  3.69  Clear  White/Grey  2.15
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Lens Finish Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture	50/60Hz  0.9  Base Up or Down -20C (-4F) to +40C (+104F)  10.75  3.69  Clear  White/Grey  2.15
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Lens Finish Housing Color Weight (lb.)  Additional Information  Rated For Enclosed Fixture IP Rating	50/60Hz 0.9  Base Up or Down -20C (-4F) to +40C (+104F)  10.75 3.69 Clear White/Grey 2.15  Yes IP65
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Lens Finish Housing Color  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  IP Rating Warranty	50/60Hz  0.9  Base Up or Down -20C (-4F) to +40C (+104F)  10.75  3.69  Clear  White/Grey  2.15
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Lens Finish Housing Color Weight (lb.)  Additional Information  Rated For Enclosed Fixture IP Rating	50/60Hz 0.9  Base Up or Down -20C (-4F) to +40C (+104F)  10.75 3.69 Clear White/Grey 2.15  Yes IP65
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Lens Finish Housing Color  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  IP Rating Warranty	50/60Hz 0.9  Base Up or Down -20C (-4F) to +40C (+104F)  10.75 3.69 Clear White/Grey 2.15  Yes IP65
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Lens Finish Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture IP Rating Warranty  Compliance	50/60Hz  0.9  Base Up or Down -20C (-4F) to +40C (+104F)  10.75  3.69  Clear  White/Grey  2.15  Yes  IP65  5 Year Limited - Hi-Pro
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Lens Finish Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture IP Rating Warranty  Compliance Safety Listing	50/60Hz  0.9  Base Up or Down -20C (-4F) to +40C (+104F)  10.75  3.69  Clear  White/Grey  2.15  Yes  IP65  5 Year Limited - Hi-Pro
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Lens Finish Housing Color Weight (lb.)  Additional Information  Rated For Enclosed Fixture IP Rating Warranty  Compliance  Safety Listing Location Rating	50/60Hz  0.9  Base Up or Down -20C (-4F) to +40C (+104F)  10.75  3.69  Clear  White/Grey  2.15  Yes  IP65  5 Year Limited - Hi-Pro  cULus - Listed  Wet
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Lens Finish Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture IP Rating Warranty  Compliance Safety Listing Location Rating Energy Star	50/60Hz  0.9  Base Up or Down -20C (-4F) to +40C (+104F)  10.75  3.69  Clear  White/Grey  2.15  Yes  IP65  5 Year Limited - Hi-Pro  CULus - Listed  Wet  No
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Lens Finish Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture IP Rating Warranty  Compliance Safety Listing Location Rating Energy Star DLC Approved	50/60Hz  0.9  Base Up or Down -20C (-4F) to +40C (+104F)  10.75  3.69  Clear  White/Grey  2.15  Yes  IP65  5 Year Limited - Hi-Pro  cULus - Listed  Wet  No  No
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Lens Finish Housing Color Weight (lb.)  Additional Information  Rated For Enclosed Fixture IP Rating Warranty  Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale	50/60Hz  0.9  Base Up or Down -20C (-4F) to +40C (+104F)  10.75  3.69  Clear  White/Grey  2.15  Yes  IP65  5 Year Limited - Hi-Pro  CULus - Listed  Wet  No  No  Exempt - Base Not Regulated
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Lens Finish Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture IP Rating Warranty  Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale California Status	50/60Hz  0.9  Base Up or Down  -20C (-4F) to +40C (+104F)  10.75  3.69  Clear  White/Grey  2.15  Yes  IP65  5 Year Limited - Hi-Pro  cULus - Listed  Wet  No  No  Exempt - Base Not Regulated  Lawful for sale in California

Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: <a href="https://www.satco.com/">https://www.satco.com/</a>



