SATCO' NUVO

Project Name

Prepared By



SATCO S29679 90W/LED/HID/MB/5000K/100-277V

Notes

General	
Status	Discontinued
Substitute	S39679
Watts	90W
Incandescent Equivalent	750W
Fluorescent Equivalent	200W
HID Equivalent	600W
Volts	120V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	11700L
Beam Spread	360
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Corncob
Technology	LED
Min Compartment Size	Length: 22 in. Width: 17 in. Depth: 17 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	50/60Hz
Power Factor	>0.9
Operating Position	Base Up or Down
Surge Protection	Built-in surge protection - 4KV
Operating Temperature	-20C (-4F) to +65C (+149F)
Physical	
Physical MOL MOD	<u>10.03</u> 4.94
MOL MOD	10.03 4.94
MOL MOD Lens Finish	10.03
MOL MOD	10.03 4.94 Clear
MOL MOD Lens Finish Housing Color	10.03 4.94 Clear White
MOL MOD Lens Finish Housing Color Weight (Ib.) Additional Information Additional Info	10.03 4.94 Clear White 3.48 Width 360 deg 4.91 in.; Width 270 deg 10.87 in.; Width 180 deg 12.60 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg)
MOL MOD Lens Finish Housing Color Weight (Ib.) Additional Information Additional Info Rated For Enclosed Fixture	10.03 4.94 Clear White 3.48 Width 360 deg 4.91 in.; Width 270 deg 10.87 in.; Width 180 deg 12.60 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes
MOL MOD Lens Finish Housing Color Weight (Ib.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating	10.03 4.94 Clear White 3.48 Width 360 deg 4.91 in.; Width 270 deg 10.87 in.; Width 180 deg 12.60 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65
MOL MOD Lens Finish Housing Color Weight (Ib.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes	10.03 4.94 Clear White 3.48 Width 360 deg 4.91 in.; Width 270 deg 10.87 in.; Width 180 deg 12.60 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures.
MOL MOD Lens Finish Housing Color Weight (Ib.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating	10.03 4.94 Clear White 3.48 Width 360 deg 4.91 in.; Width 270 deg 10.87 in.; Width 180 deg 12.60 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65
MOL MOD Lens Finish Housing Color Weight (Ib.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes	10.03 4.94 Clear White 3.48 Width 360 deg 4.91 in.; Width 270 deg 10.87 in.; Width 180 deg 12.60 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures.
MOL MOD Lens Finish Housing Color Weight (Ib.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty	10.03 4.94 Clear White 3.48 Width 360 deg 4.91 in.; Width 270 deg 10.87 in.; Width 180 deg 12.60 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures.
MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance	10.03 4.94 Clear White 3.48 Width 360 deg 4.91 in.; Width 270 deg 10.87 in.; Width 180 deg 12.60 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. 5-Years cULus - Certified; cULus - Classified; cULus -
MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing	10.03 4.94 Clear White 3.48 Width 360 deg 4.91 in.; Width 270 deg 10.87 in.; Width 180 deg 12.60 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. 5-Years cULus - Certified; cULus - Classified; cULus - Listed
MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating	10.03 4.94 Clear White 3.48 Width 360 deg 4.91 in.; Width 270 deg 10.87 in.; Width 180 deg 12.60 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. 5-Years cULus - Certified; cULus - Classified; cULus - Listed Damp
MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved	10.03 4.94 Clear White 3.48 Width 360 deg 4.91 in.; Width 270 deg 10.87 in.; Width 180 deg 12.60 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. 5-Years CULus - Certified; cULus - Classified; cULus - Listed Damp No
MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status	10.03 4.94 Clear White 3.48 Width 360 deg 4.91 in.; Width 270 deg 10.87 in.; Width 180 deg 12.60 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. 5-Years CULus - Certified; cULus - Classified; cULus - Listed Damp No Lawful for sale in California
MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status	10.03 4.94 Clear White 3.48 Width 360 deg 4.91 in.; Width 270 deg 10.87 in.; Width 180 deg 12.60 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. 5-Years CULus - Certified; cULus - Classified; cULus - Listed Damp No Lawful for sale in California Lawful for sale
MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status	10.03 4.94 Clear White 3.48 Width 360 deg 4.91 in.; Width 270 deg 10.87 in.; Width 180 deg 12.60 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. 5-Years CULus - Certified; cULus - Classified; cULus - Listed Damp No Lawful for sale in California Lawful for sale Lawful for sale
MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status	10.03 4.94 Clear White 3.48 Width 360 deg 4.91 in.; Width 270 deg 10.87 in.; Width 180 deg 12.60 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. 5-Years CULus - Certified; cULus - Classified; cULus - Listed Damp No Lawful for sale in California Lawful for sale Lawful for sale Lawful for sale Lawful for sale
MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status	10.03 4.94 Clear White 3.48 Width 360 deg 4.91 in.; Width 270 deg 10.87 in.; Width 180 deg 12.60 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. 5-Years CULus - Certified; cULus - Classified; cULus - Listed Damp No Lawful for sale in California Lawful for sale
MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status	10.03 4.94 Clear White 3.48 Width 360 deg 4.91 in.; Width 270 deg 10.87 in.; Width 180 deg 12.60 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. 5-Years CULus - Certified; cULus - Classified; cULus - Listed Damp No Lawful for sale in California Lawful for sale
MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status Vermont Status	10.03 4.94 Clear White 3.48 Width 360 deg 4.91 in.; Width 270 deg 10.87 in.; Width 180 deg 12.60 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. 5-Years CULus - Certified; cULus - Classified; cULus - Listed Damp No Lawful for sale in California Lawful for sale Lawful for sale

