

Project Name

Location

Prepared By



## SATCO S29750

30W/LED/HID/MB/5000K/100-277V

### Notes

[www] 04-02-2023 09:30:02

### General

|                         |  |
|-------------------------|--|
| Status                  | Discontinued                             |
| Substitute              | S39750                                   |
| Watts                   | 30W                                      |
| Incandescent Equivalent | 200W                                     |
| Fluorescent Equivalent  | 55W                                      |
| HID Equivalent          | 150W                                     |
| Volts                   | 120V-277V                                |
| Shape                   | Corncob                                  |
| Base                    | Medium                                   |
| ANSI Base               | E26                                      |
| Finish                  | Clear                                    |
| CCT (Kelvin)            | 5000K                                    |
| Temperature             | Natural Light                            |
| CRI                     | 80+                                      |
| Lumens                  | 3900L                                    |
| Beam Spread             | 360                                      |
| Dimmable                | Non-Dimmable                             |
| Hours Rated             | 50000                                    |
| Product Category        | Corncob                                  |
| Technology              | LED                                      |
| Min Compartment Size    | Length: 11 in. Width: 8 in. Depth: 8 in. |
| Ballasting Requirements | Ballast Bypass                           |

### Electrical

|                       |                                 |
|-----------------------|---------------------------------|
| Operating Frequency   | 50/60Hz                         |
| Power Factor          | >0.9                            |
| Operating Position    | Base Up or Down                 |
| Surge Protection      | Built-in surge protection - 2KV |
| Operating Temperature | -25C (-13F) to +45C (+113F)     |

### Physical

|               |       |
|---------------|-------|
| MOL           | 6.38  |
| MOD           | 3.19  |
| Lens Finish   | Clear |
| Housing Color | White |
| Weight (lb.)  | 1.37  |

### Additional Information

|                            |  |
|----------------------------|--|
| Additional Info            | Width 360 deg 3.2 in.; Width 270 deg 6.8 in.; Width 180 deg 7.7 in.          |
| Rated For Enclosed Fixture | Yes  |
| IP Rating                  | IP65   |
| Installation Notes         | Not for use in vapor tight fixtures. Arms fully open diameter is 7.69 inches |
| Warranty                   | 5 Year Limited - Hi-Pro  |

### Compliance

|                      |   |
|----------------------|---|
| Safety Listing       | cULus - Certified; cULus - Classified; cULus - Listed |
| Location Rating      | Damp  |
| DLC Approved         | No  |
| California Status    | Lawful for sale in California                         |
| Title 20 / 24 Status | Lawful for sale                                       |
| Colorado Status      | Lawful for sale                                       |
| Hawaii Status        | Lawful for sale                                       |
| Nevada Status        | Lawful for sale                                       |
| Vermont Status       | Lawful for sale                                       |
| Washington Status    | Lawful for sale                                       |
| RoHS Compliant       | Yes   |
| FCC Compliant        | Yes   |
| SDS Sheet            | LED_Lamp  |