SATCO NUVO

Project Name

ocation

Prepared By



Notes

60W/LED/HID/MB/5000K/100-277V

ww1 07-07-2025 00:13:

General	
Status	Discontinued
Substitute	S39752
Watts	60W
Incandescent Equivalent	500W
Fluorescent Equivalent	85W
HID Equivalent	250W
Volts	120V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39 Clear
Finish CCT (Valuity)	
CCT (Kelvin)	5000K
Temperature CRI	Natural Light
	80+
Lumens	7800L
Beam Spread	360
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Corncob
Technology	LED
Min Compartment Size	Length: 8.27 in. Width: 9.25 in. Depth: 9.25 in
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	50/60Hz
Power Factor	>0.9
Operating Position	Base Up or Down
Surge Protection	Built-in surge protection - 2.5KV
Operating Temperature	-25C (-13F) to +45C (+113F)
Physical	
	0.56
MOL MOD	8.56 3.81
Lens Finish	Clear
	M/h ih n
Housing Color	White
Weight (lb.)	White 2.05
Weight (lb.) Additional Information Additional Info	2.05 Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in. Approved for totally enclosed fixtures; Base up or base down
Weight (lb.) Additional Information	2.05 Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no
Weight (lb.) Additional Information Additional Info	Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg)
Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture	Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg)
Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes	Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. Arms fully
Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating	Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 9.31 inches
Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance	Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 9.31 inches
Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty	2.05 Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 9.31 inches 5-Years CULus - Certified; cULus - Classified; cULus -
Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing	2.05 Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 9.31 inches 5-Years CULus - Certified; cULus - Classified; cULus - Listed
Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved	2.05 Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 9.31 inches 5-Years CULus - Certified; cULus - Classified; cULus - Listed Damp
Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating	2.05 Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 9.31 inches 5-Years CULus - Certified; cULus - Classified; cULus - Listed Damp No
Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status	Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 9.31 inches 5-Years CULus - Certified; cULus - Classified; cULus - Listed Damp No Lawful for sale in California
Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status	Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 9.31 inches 5-Years CULus - Certified; cULus - Classified; cULus - Listed Damp No Lawful for sale in California Lawful for sale
Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status	Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 9.31 inches 5-Years CULus - Certified; cULus - Classified; cULus - Listed Damp No Lawful for sale in California Lawful for sale Lawful for sale
Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status	Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 9.31 inches 5-Years CULus - Certified; cULus - Classified; cULus - Listed Damp No Lawful for sale in California Lawful for sale Lawful for sale Lawful for sale Lawful for sale
Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status	Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 9.31 inches 5-Years CULus - Certified; cULus - Classified; cULus - Listed Damp No Lawful for sale in California Lawful for sale
Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status Washington Status	Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 9.31 inches 5-Years CULus - Certified; cULus - Classified; cULus - Listed Damp No Lawful for sale in California Lawful for sale
Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status	Width 360 deg 3.8 in.; Width 270 deg 8.2 in.; Width 180 deg 9.3 in. Approved for totally enclosed fixtures; Base up or base down operation; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 Not for use in vapor tight fixtures. Arms fully open diameter is 9.31 inches 5-Years CULus - Certified; cULus - Classified; cULus - Listed Damp No Lawful for sale in California Lawful for sale Lawful for sale

