

Project Name

Location Prepared By



SATCO S29852

9WPLH/LED/840/DR/4P

Notes

Status	Active	
Watts	9W	
Fluorescent Equivalent	26W/32W/42W	
Volts	Ballast Dependent	
Ballast Type	Type A	
Shape	PL	
Base	G24q (4-Pin)	
ANSI Base	G24q	
Finish	Frost	
CCT (Kelvin)	4000K	
Temperature	Cool White	
CRI	80+	
Lumens	1100L	
Beam Spread	120	
Dimmable	Yes-Dimmable	
Hours Rated	50000	
Product Category	PL	
Operating Position	Horizontal	
Technology	LED	

Electrical	
Ballasting Requirements	Ballast required, check compatibility
Working Voltage	Ballast dependent
Operating Frequency	50/60Hz
Dimming Note	Only Dimmable with Compatible Dimming Ballasts
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	6.63
MOD	1.09
Housing Color	White
Weight (lb.)	0.18

Additional Information	
Rated For Enclosed Fixture	Yes
Warranty	5-Years

CULus Damp
<u> </u>
Yes
PLTQJ675TIRG
Lawful for sale in California
Lawful for sale
Yes
Yes