

Project Name

Location

Prepared By



SATCO S29860

9WPLV/LED/840/DR/4P

Notes

[www] 04-07-2023 09:17:00

General

Status	Active
Watts	9W
Fluorescent Equivalent	18W/26W/32W/42W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	PL
Base	G24q (4-Pin)
ANSI Base	G24q
Finish	Frost
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	1100L
Beam Spread	120
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	PL
Operating Position	Base Up or Down
Technology	LED

Electrical

Ballasting Requirements	Ballast required
Working Voltage	Ballast dependent
Operating Frequency	50/60Hz
Dimming Note	Only Dimmable with Compatible Dimming Ballasts
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	4.69
MOD	1.91
Housing Color	White
Weight (lb.)	0.23

Additional Information

Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - 10 hr per day

Compliance

Safety Listing	cULus
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLZ5IXXDQS03
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
Canadian Standard ICES-005	Yes
SDS Sheet	LED_Lamp