SATCO NUVO

Project Name

.

Location Prepared By

SATCO S29934 STRALEDING ADDOR 10W SHOR 1790w Controlling with classifier matter balant, schedi for programmed start and raged the

SATCO S29934

12T8/LED/48-830/DR

Notes

Status	Discontinued
Substitute	
Watts	12W
Incandescent Equivalent	60W
Fluorescent Equivalent	25W-32W
Volts	Ballast Dependent
Ballast Type	Туре А
Shape	Т8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss
CCT (Kelvin)	3000K
Temperature	Warm White
CRI	80+
Lumens	1700L
Beam Spread	210
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED
rechnology	
Electrical	
Ballasting Requirements	Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required.May not be compatible with every ballast. Refer to the ballast compatibility chart
Power Factor	0.9
Operating Temperature	-20C (-4F) to +45C (+113F)
Physical	
Titysical	
MOL	48
MOD	1
Lens Finish	Gloss
Additional Information	
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years
-	
Compliance	
Safety Listing	cULus
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes

