

Project Name

Location

Prepared By



# SATCO S29977

15T8/LED/48-840/DR

## Notes

(www) 09-14-2023 23:00:14

## General

Status	Discontinued
Substitute	S49977R1
Watts	15W
Incandescent Equivalent	100W
Fluorescent Equivalent	25W-32W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	2200L
Beam Spread	210
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

## Electrical

Ballasting Requirements	Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart
Power Factor	0.9
Operating Temperature	-20C (-4F) to +45C (+113F)

## Physical

MOL	48
MOD	1
Lens Finish	Gloss

## Additional Information

Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years

## Compliance

Safety Listing	cULus
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp