

Project Name

Location

Prepared By



## SATCO S33115

130W/LED/HID-HB/5K/100-277V

### Notes

(www) 03-28-2023 09:13:09

### General

Status	Active
Watts	80W/100W/130W
Incandescent Equivalent	400W
HID Equivalent	250W/320W/400W
Volts	120V-277V
Shape	Hi-Bay
Base	Mogul Extended
ANSI Base	EX39
Finish	White
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	11200L/14000L/18200L
Beam Spread	120
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Min Compartment Size	Length: 15.75 in. Width: 14.96 in.
Ballasting Requirements	Ballast Bypass

### Electrical

Operating Frequency	50/60Hz
Power Factor	0.99
Operating Position	Universal
Surge Protection	Built-in surge protection - 4KV
Operating Temperature	-25C (-13F) to +50C (+122F)

### Physical

MOL	9.72
MOD	5.51
Housing Color	White
Weight (lb.)	2.7

### Additional Information

Rated For Enclosed Fixture	Yes
IP Rating	IP64
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5 Year Limited - Hi-Pro

### Compliance

Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp