

Project Name

Location

Prepared By



SATCO S33117

150W/LED/HID-HB/5K/100-277V

Notes

1www|10-27-2025 05:20:50

General

| | |
|-------------------------|------------------------------------|
| Status | Active |
| Watts | 100W/120W/150W |
| Incandescent Equivalent | 400W |
| HID Equivalent | 320W/400W/600W |
| Volts | 120V-277V |
| Shape | Corncob |
| Base | Mogul Extended |
| ANSI Base | EX39 |
| Finish | White |
| CCT (Kelvin) | 5000K |
| Temperature | Natural Light |
| CRI | 80+ |
| Lumens | 14000L/16800L/21000L |
| Beam Spread | 120 |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Product Category | LED HID |
| Technology | LED |
| Min Compartment Size | Length: 15.75 in. Width: 14.96 in. |
| Ballasting Requirements | Ballast Bypass |

Electrical

| | |
|-----------------------|---------------------------------|
| Operating Frequency | 50/60Hz |
| Power Factor | 0.99 |
| Operating Position | Universal |
| Surge Protection | Built-in surge protection - 4KV |
| Operating Temperature | -25C (-13F) to +50C (+122F) |

Physical

| | |
|---------------|-------|
| MOL | 10.31 |
| MOD | 5.51 |
| Housing Color | White |
| Weight (lb.) | 2.92 |

Additional Information

| | |
|----------------------------|--------------------------------------|
| Rated For Enclosed Fixture | Yes |
| IP Rating | IP64 |
| Installation Notes | Not for use in vapor tight fixtures. |
| Warranty | 5-Years |

Compliance

| | |
|----------------------|---|
| Safety Listing | cULus - Certified; cULus - Classified; cULus - Listed |
| Location Rating | Damp |
| DLC Approved | No |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| SDS Sheet | LED_Lamp |