SATCO NUVO

Project Name

Location

Prepared By



SATCO S39392

36W/LED/HID/5000K/100-277V E26

Notes

www] 05-15-2024 04:42:5

Compliance

General	
Status	Discontinued
Substitute	S49392
Watts	36W
Incandescent Equivalent	200W
Fluorescent Equivalent	55W
HID Equivalent	150W
Volts	100V-277V
Shape	Corncob
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80
Lumens	5148L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Corncob
Technology	LED
Min Compartment Size	Length: 8.5 in. Width: 6 in. Depth: 6 in.
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	
Electrical Working Voltage	AC 90-305V
	AC 90-305V 50/60Hz
Working Voltage	
Working Voltage Operating Frequency	50/60Hz
Working Voltage Operating Frequency Power Factor	50/60Hz >0.9
Working Voltage Operating Frequency Power Factor Operating Position	50/60Hz >0.9 Universal
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection	50/60Hz >0.9 Universal Built-in surge protection - 4KV
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature	50/60Hz >0.9 Universal Built-in surge protection - 4KV
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 7.34
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 7.34 3.34
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 7.34 3.34 Clear
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 7.34 3.34 Clear Plastic (PS)
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 7.34 3.34 Clear Plastic (PS) White
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 7.34 3.34 Clear Plastic (PS) White
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 7.34 3.34 Clear Plastic (PS) White 1.52 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 7.34 3.34 Clear Plastic (PS) White 1.52 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 7.34 3.34 Clear Plastic (PS) White 1.52 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 7.34 3.34 Clear Plastic (PS) White 1.52 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes IP64 DLC 5.1 replacement S23149;
Working Voltage Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Specification Note	50/60Hz >0.9 Universal Built-in surge protection - 4KV -25C (-13F) to +45C (+113F) 7.34 3.34 Clear Plastic (PS) White 1.52 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes IP64 DLC 5.1 replacement S23149; Non-DLC replacement S49392

Safety Listing	cULus - Listed
Location Rating	Damp
Energy Star	No
DLC Approved	No
CA T20 / T24 Rationale	Exempt - >2600 Lumens
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



