SATCO NUVO

Project Name

Location

Prepared By



Notes

General	
Status	Discontinued
Substitute	S49670
Watts	18W
	120W
Incandescent Equivalent	32W
Fluorescent Equivalent	70W
HID Equivalent Volts	
	100V-277V
Shape	Corncob
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	80
Lumens	2340L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 6 in. Width: 8.5 in. Height: 6 in.
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	
Working Voltage	AC 90-305V
TOTAL TOTAL	AO 30-303 V
Operating Frequency	50/60Hz
Operating Frequency	50/60Hz
Operating Frequency Power Factor	50/60Hz >0.9
Operating Frequency Power Factor Operating Position	50/60Hz >0.9 Universal
Operating Frequency Power Factor Operating Position Surge Protection	50/60Hz >0.9 Universal Built-in surge protection - 2.5KV
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature	50/60Hz >0.9 Universal Built-in surge protection - 2.5KV
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical	50/60Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to +45C (+113F) 5.69
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD	50/60Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to +45C (+113F) 5.69 2.38
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish	50/60Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to +45C (+113F) 5.69 2.38 Clear
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material	50/60Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to +45C (+113F) 5.69 2.38 Clear Plastic (PS)
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish	50/60Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to +45C (+113F) 5.69 2.38 Clear
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	50/60Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to +45C (+113F) 5.69 2.38 Clear Plastic (PS) White
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	50/60Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to +45C (+113F) 5.69 2.38 Clear Plastic (PS) White
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	50/60Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to +45C (+113F) 5.69 2.38 Clear Plastic (PS) White 0.66 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	50/60Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to +45C (+113F) 5.69 2.38 Clear Plastic (PS) White 0.66 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info	50/60Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to +45C (+113F) 5.69 2.38 Clear Plastic (PS) White 0.66 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating	50/60Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to +45C (+113F) 5.69 2.38 Clear Plastic (PS) White 0.66 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes IP64 DLC 5.1 replacement S23146;
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Specification Note	50/60Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to +45C (+113F) 5.69 2.38 Clear Plastic (PS) White 0.66 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes IP64 DLC 5.1 replacement S23146; Non-DLC replacement S49670
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Specification Note Shatter-Proof Type	50/60Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to +45C (+113F) 5.69 2.38 Clear Plastic (PS) White 0.66 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes IP64 DLC 5.1 replacement S23146; Non-DLC replacement S49670 Shatter resistant materials
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Specification Note Shatter-Proof Type Warranty	50/60Hz >0.9 Universal Built-in surge protection - 2.5KV -25C (-13F) to +45C (+113F) 5.69 2.38 Clear Plastic (PS) White 0.66 Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes IP64 DLC 5.1 replacement S23146; Non-DLC replacement S49670 Shatter resistant materials

Location Rating	Damp
Energy Star	No
DLC Approved	No
CA T20 / T24 Rationale	Non-Compliant - <45 LPW
California Status	Non-Compliant
Title 20 / 24 Status	Non-Compliant
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



