## SATCO NUVO

Project Name

ocation

Prepared By



Notes

rww1 03-31-2025 00:32:5

Status	Discontinued
Substitute	S49675
Watts	80W
ncandescent Equivalent	400W
Fluorescent Equivalent	100W
HID Equivalent	320W
Volts	120V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	11200L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Corncob
Technology	LED
Min Compartment Size	Length: 17.32 in. Width: 9.25 in. Depth: 9.25
	in.  Pallact Punass Direct wire only 100V 277V
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	
Working Voltage	AC 100-277V
Operating Frequency	50/60Hz
Power Factor	>0.9
Operating Position	Base Up or Down
Surge Protection	Built-in surge protection - 6KV
Thermal Management	Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).
Operating Temperature	-25C (-13F) to +45C (+113F)
Physical	
MOL	8.78
MOD	4.72
Lens Finish	Clear
Lens Material	Plastic (PS)
Housing Color	White
Weight (lb.)	3.2
Additional Information	
Additional Info	Emits no UV light; Contains no Mercury (Hg) Acceptable for use in food prep areas
Rated For Enclosed Fixture	Yes
P Rating	IP64
Specification Note	DLC 5.1 replacement S23143; Non-DLC replacement S49675
nstallation Notes	Not for use in vapor tight fixtures.
	Shatter resistant materials
Shatter-Proof Type	

Shatter-Proof Type	Shatter resistant materials
Warranty	5 Year Limited - Hi-Pro
Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale

Yes

Yes

LED\_Lamp



RoHS Compliant

FCC Compliant

SDS Sheet