SATCO NUVO

Project Name

Location

Prepared By



ww] 05-15-2024 04:42:5

Installation Notes

Comoval	
General	
Status	Discontinued
Substitute	S49677
Watts	120W
Incandescent Equivalent	750W
Fluorescent Equivalent	200W
HID Equivalent	600W
Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80
Lumens	16800L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Corncob
Technology	LED
Min Compartment Size	Length: 17.32 in. Width: 9.25 in. Depth: 9.25 in.
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	
Working Voltage	AC 100-277V
Operating Frequency	50/60Hz
Power Factor	>0.9
Operating Position	Base Up or Down
Surge Protection	Built-in surge protection - 6KV
Thermal Management	Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).
Operating Temperature	-25C (-13F) to +45C (+113F)
Physical	
MOL	10.34
MOD	4.72
Lens Finish	Clear
Lens Material	Plastic (PS)
Housing Color	White
Weight (lb.)	3.69
Additional Information	
Additional information	
Additional Info	Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas
Rated For Enclosed Fixture	Yes
IP Rating	IP64
Specification Note	DLC 5.1 replacement S23145; Non-DLC replacement S49677

Not for use in vapor tight fixtures.

Warranty	5 Year Limited - Hi-Pro	
Compliance		
Safety Listing	cULus - Listed	
Location Rating	Damp	
Energy Star	No	
DLC Approved	No	
CA T20 / T24 Rationale	Exempt - Base Not Regulated	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
Colorado Status	Lawful for sale	
Hawaii Status	Lawful for sale	
Nevada Status	Lawful for sale	
Vermont Status	Lawful for sale	
Washington Status	Lawful for sale	
RoHS Compliant	Yes	
FCC Compliant	Yes	
SDS Sheet	LED_Lamp	

Shatter resistant materials

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/

Shatter-Proof Type



