

Project Name

ocation Prepared By



SATCO S39900

9T8/LED/24-830/BP/SE-DE

Notes

v] 10-27-2025 05:2

Status	Active	
Watts	9W	
Incandescent Equivalent	40W	
· · · · · · · · · · · · · · · · · · ·	17W	
Fluorescent Equivalent		
Volts	120V-277V	
Ballast Type	Туре В	
Shape	T8	
Base	Medium Bi Pin	
ANSI Base	G13	
Nominal Length	24	
Finish	Gloss White	
CCT (Kelvin)	3000K	
Temperature	Warm White	
CRI	80+	
Lumens	1100L	
Beam Spread	210	
Hours Rated	50000	
Product Category	Linear	
Technology	LED	

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical		
MOL	23.78	
MOD	1.1	
Material	Glass	
Lens Finish	Gloss White	
Lens Material	Glass	
Housing Color	White	
Weight (lb.)	0.24	

Additional Information		
Additional Info	Equivalent CCT selectable option available in S11764	
Tube Guard Use	Yes	
Installation Notes	Not for use in vapor tight fixtures.	
Specification Note	Built-in shock resistant circuit - (not hot until both ends are installed)	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cRUus - Recognized Component
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLVVYBG8LEVK
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp