

Project Name

ocation Prepared By



SATCO S39901

9T8/LED/24-835/BP/SE-DE

Notes

w1 10-27-2025 05:1

Status	Active
Watts	9W
Incandescent Equivalent	40W
Fluorescent Equivalent	17W
Volts	120V-277V
Ballast Type	Туре В
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	24
Finish	Gloss White
CCT (Kelvin)	3500K
Temperature	Neutral White
CRI	80+
Lumens	1100L
Beam Spread	210
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical		
MOL	23.78	
MOD	1.1	
Material	Glass	
Lens Finish	Gloss White	
Lens Material	Glass	
Housing Color	White	
Weight (lb.)	0.24	

Additional Information	
Additional Info	Equivalent CCT selectable option available in S11764
Tube Guard Use	Yes
Installation Notes	Not for use in vapor tight fixtures.
Specification Note	Built-in shock resistant circuit - (not hot until both ends are installed)
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cRUus - Recognized Component
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLSLJY8NLUXI
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp