

Project Name

Location Prepared By



17T8/LED/48-830/BP/SE-DE

## Notes

General	
Status	Active
Watts	17W
	90W
Incandescent Equivalent	45W
Fluorescent Equivalent Volts	120V-277V
Ballast Type	Type B T8
Shape Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss White
	3000K
CCT (Kelvin)	Warm White
Temperature	
CRI	82
Lumens	2100L
Beam Spread	210
Hours Rated	50000
Product Category	
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)
Physical	
MOL	47.78
MOD	1.1
	1.1 Glass
MOD	
MOD Material	Glass
MOD Material Lens Finish Lens Material	Glass Gloss White
MOD Material Lens Finish	Glass Gloss White Glass
MOD Material Lens Finish Lens Material Housing Color Weight (lb.)	Glass Gloss White Glass White
MOD Material Lens Finish Lens Material Housing Color	Glass Gloss White Glass White
MOD Material Lens Finish Lens Material Housing Color Weight (lb.)	Glass Gloss White Glass White
MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	Glass Gloss White Glass White 0.44  Equivalent CCT selectable option available in S11767 Approved for use with tube guards
MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info	Glass Gloss White Glass White 0.44  Equivalent CCT selectable option available in S11767
MOD Material Lens Finish Lens Material Housing Color Weight (lb.)  Additional Information  Additional Info	Glass Gloss White Glass White 0.44  Equivalent CCT selectable option available in S11767 Approved for use with tube guards
MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Tube Guard Use  Installation Notes	Glass Gloss White Glass White 0.44  Equivalent CCT selectable option available in S11767 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not
MOD Material Lens Finish Lens Material Housing Color Weight (lb.)  Additional Information  Additional Info Tube Guard Use Installation Notes  Specification Note	Glass Gloss White Glass White 0.44  Equivalent CCT selectable option available in S11767 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs -
MOD Material Lens Finish Lens Material Housing Color Weight (lb.)  Additional Information  Additional Info Tube Guard Use Installation Notes  Specification Note  Warranty	Glass Gloss White Glass White 0.44  Equivalent CCT selectable option available in S11767 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass  CULus - Classified; cRUus -
MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Tube Guard Use Installation Notes  Specification Note  Warranty  Compliance  Safety Listing	Glass Gloss White Glass White 0.44  Equivalent CCT selectable option available in S11767 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass  CULus - Classified; cRUus - Recognized Component
MOD Material Lens Finish Lens Material Housing Color Weight (lb.)  Additional Information  Additional Info Tube Guard Use Installation Notes  Specification Note  Warranty  Compliance  Safety Listing  Location Rating	Glass Gloss White Glass White 0.44  Equivalent CCT selectable option available in S11767 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass  CULus - Classified; cRUus - Recognized Component Damp
MOD Material Lens Finish Lens Material Housing Color Weight (lb.)  Additional Information  Additional Info Tube Guard Use Installation Notes  Specification Note  Warranty  Compliance  Safety Listing Location Rating Energy Star	Glass Gloss White Glass White 0.44  Equivalent CCT selectable option available in S11767 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass  CULus - Classified; cRUus - Recognized Component Damp No
MOD  Material  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Tube Guard Use Installation Notes  Specification Note  Warranty  Compliance  Safety Listing  Location Rating	Glass Gloss White Glass White 0.44  Equivalent CCT selectable option available in S11767 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass  CULus - Classified; cRUus - Recognized Component Damp

CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: <a href="https://www.satco.com/">https://www.satco.com/</a>



