

Project Name

Location Prepared By



SATCO S39906

17T8/LED/48-840/BP/SE-DE

Notes

DLC ID

General	
	Astina
Status	Active
Watts	17W
Incandescent Equivalent	90W
Fluorescent Equivalent	45W
Volts	120V-277V
Ballast Type	Type B
Shape	<u>T8</u>
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48 Olasa White
Finish	Gloss White
CCT (Kelvin)	4000K
Temperature	Cool White
CRI .	82
Lumens	2200L
Beam Spread	210
Hours Rated	50000
Product Category	<u>T8</u>
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)
Operating Temperature Physical	-20C (-4F) to +45C (+113F)
	-20C (-4F) to +45C (+113F)
Physical	
Physical MOL	47.78
Physical MOL MOD	47.78 1.1
Physical MOL MOD Material	47.78 1.1 Glass
Physical MOL MOD Material Lens Finish	47.78 1.1 Glass Gloss White
Physical MOL MOD Material Lens Finish Lens Material	47.78 1.1 Glass Gloss White Glass
Physical MOL MOD Material Lens Finish Lens Material Housing Color	47.78 1.1 Glass Gloss White Glass White
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.)	47.78 1.1 Glass Gloss White Glass White
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	47.78 1.1 Glass Gloss White Glass White 0.44 Equivalent CCT selectable option available in S11767
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Use	47.78 1.1 Glass Gloss White Glass White 0.44 Equivalent CCT selectable option available in S11767 Approved for use with tube guards
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	47.78 1.1 Glass Gloss White Glass White 0.44 Equivalent CCT selectable option available in S11767 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Installation Notes	47.78 1.1 Glass Gloss White Glass White 0.44 Equivalent CCT selectable option available in S11767 Approved for use with tube guards Not for use in vapor tight fixtures.
MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Use Installation Notes Specification Note	47.78 1.1 Glass Gloss White Glass White 0.44 Equivalent CCT selectable option available in S11767 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs -
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Installation Notes Specification Note Warranty	47.78 1.1 Glass Gloss White Glass White 0.44 Equivalent CCT selectable option available in S11767 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs -
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Installation Notes Specification Note Warranty Compliance	47.78 1.1 Glass Gloss White Glass White 0.44 Equivalent CCT selectable option available in S11767 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass cULus - Classified; cRUus -
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Installation Notes Specification Note Warranty Compliance Safety Listing	47.78 1.1 Glass Gloss White Glass White 0.44 Equivalent CCT selectable option available in S11767 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass cULus - Classified; cRUus - Recognized Component
Physical MOL MOD Material Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Installation Notes Specification Note Warranty Compliance Safety Listing Location Rating	47.78 1.1 Glass Gloss White Glass White 0.44 Equivalent CCT selectable option available in S11767 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass cULus - Classified; cRUus - Recognized Component Damp

PLTZ18KVOPQ7

CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



