

Project Name

Location

Prepared By



SATCO S39918

15T8/LED/48-835/BP/SE-DE

Notes

[www] 01-08-2023 09:14:14

General	
Status	Active
Watts	15W
Fluorescent Equivalent	25W/28W/30W/32W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss White
CCT (Kelvin)	3500K
Temperature	Neutral White
CRI	82
Lumens	2100L
Beam Spread	210
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	>0.9
THD	<20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	47.78
MOD	1
Material	Glass
Weight (lb.)	0.46

Additional Information	
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

Compliance	
Safety Listing	cULus - Classified; cRUus - Recognized Component
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-2VHDVL
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes