SATCO NUVO

Project Name

ocation Prepared By



Notes

v] 10-27-2025 05:20

Status	Active	
Watts	15W	
Incandescent Equivalent	75W	
Fluorescent Equivalent	25W/28W/30W/32W	
Volts	120V-277V	
Ballast Type	Туре В	
Shape	Т8	
Base	Medium Bi Pin	
ANSI Base	G13	
Nominal Length	48	
Finish	Gloss White	
CCT (Kelvin)	5000K	
Temperature	Natural Light	
CRI	80+	
Lumens	2200L	
Beam Spread	210	
Dimmable	Non-Dimmable	
Hours Rated	50000	
Product Category	Linear	
Technology	LED	

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	>0.9
THD	<20%
Operating Temperature	-20C (-4F) to +45C (+113F)
Physical	

Physical	
MOL	47.78
MOD	1
Material	Glass
Housing Color	White
Weight (lb.)	0.46

Additional Information		
Installation Notes	Not for use in vapor tight fixtures.	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance	
Safety Listing	cULus - Classified; cRUus - Recognized Component
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-1MX4D8
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp