SATCO NUVO

Project Name

Prepared By



Notes

General	
Status	Discontinued
Substitute	\$49977R1
Watts	15W
Incandescent Equivalent	100W
Fluorescent Equivalent	25W-32W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss White
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	2200L
Beam Spread	210
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED
Electrical	
	Ballast required. Direct Replacement-for use
Ballasting Requirements	on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible
- ·	with every ballast. Refer to the ballast compatibility chart
Dimming Note	with every ballast. Refer to the ballast
	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for
Dimming Note	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Dimming Note Power Factor	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9
Dimming Note Power Factor Operating Temperature	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9
Dimming Note Power Factor Operating Temperature Physical	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F)
Dimming Note Power Factor Operating Temperature Physical MOL	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F)
Dimming Note Power Factor Operating Temperature Physical MOL MOD	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1
Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1
Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White
Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures.
Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Rated For Enclosed Fixture	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. Yes
Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Rated For Enclosed Fixture Warranty	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. Yes
Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. Yes 5-Years
Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. Yes 5-Years
Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved California Status	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. Yes 5-Years cULus Damp No Lawful for sale in California
Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. Yes 5-Years cULus Damp No Lawful for sale in California Lawful for sale
Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. Yes 5-Years cULus Damp No Lawful for sale in California Lawful for sale Lawful for sale
Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. Yes 5-Years CULus Damp No Lawful for sale in California Lawful for sale Lawful for sale Lawful for sale
Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status	with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. Yes 5-Years cULus Damp No Lawful for sale in California Lawful for sale Lawful for sale

Warranty	5-Years
Compliance	
Safety Listing	cULus
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED Lamp