SATCO NUVO

Project Name

ocation

Prepared By



Notes

rw1 10-27-2025 05:20

| General | |
|-------------------------|--|
| Status | Active |
| Watts | 80W |
| Incandescent Equivalent | 400W |
| HID Equivalent | 320W |
| Volts | 120V-277V |
| Shape | Corncob |
| Base | Mogul Extended |
| ANSI Base | EX39 |
| Finish | White |
| CCT (Kelvin) | 4000K |
| Temperature | Cool White |
| CRI | 80+ |
| Lumens | 10960L |
| Beam Spread | 300 |
| Dimmable | Non-Dimmable |
| Hours Rated | 35000 |
| Product Category | LED HID |
| Technology | LED |
| Min Compartment Size | Length: 9.25 in. Width: 9.25 in. Height: 17.32 in. |
| Ballasting Requirements | Ballast Bypass |
| Electrical | |
| Operating Frequency | 50/60Hz |
| Power Factor | >0.9 |
| Operating Position | Base Up or Down |

| >0.9 |
|---------------------------------|
| Base Up or Down |
| Built-in surge protection - 4KV |
| -30C (-22F) to +50C (+122F) |
| |
| 8.69 |
| |

| Physical | |
|---------------------|--------------------|
| MOL | 8.69 |
| MOD | 4.72 |
| Lens Finish | Clear |
| Lens Material | Polycarbonate (PC) |
| Housing Color | White |
| Photocell or Sensor | No |
| Weight (lb.) | 3 |

| Additional Information | |
|----------------------------|---|
| Additional Info | Safety cable provided with S49395, S49396, S49397, S49675, S49676, S49677 ONLY and is required upon installation of these high bay, base-up applications. (Please See Instructions) |
| Includes | Safety Cable |
| Rated For Enclosed Fixture | Yes |
| IP Rating | IP65 |
| Installation Notes | Not for use in vapor tight fixtures. |
| Warranty | 5-Years |

| Compliance | |
|----------------------|--|
| Safety Listing | cULus - Certified; cULus - Classified; cULus - Listed |
| Location Rating | Damp |
| DLC Approved | No |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| SDS Sheet | LED_Lamp |

