

Notes

w1 04-02-2025 00:35:0

Status	Active	
Watts	8W	
Incandescent Equivalent	110W	
Fluorescent Equivalent	17W/15W	
Volts	Ballast Dependent	
Ballast Type	Туре А	
Shape	Т8	
Base	Medium Bi Pin	
ANSI Base	G13	
Nominal Length	24	
Finish	Gloss White	
CCT (Kelvin)	3500K	
Temperature	Neutral White	
CRI	80+	
Lumens	1250L	
Beam Spread	210	
Dimmable	Yes-Dimmable	
Hours Rated	50000	
Product Category	Linear	
Technology	LED	

Electrical	
Ballasting Requirements	Ballast required
Operating Frequency	50/60Hz
Dimming Note	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Power Factor	0.9
THD	20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	23.78
MOD	1.1
Material	Glass
Lens Finish	Gloss White
Lens Material	Glass
Housing Color	White
Weight (lb.)	0.22

Additional Information	
Tube Guard Use	Approved for use with tube guards when operated on Low or Normal ballast factor systems
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - T8 LED Bulbs

Compliance	
Safety Listing	cULus - Certified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	PLFWYWU1CBAG
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
Canadian Standard ICES-005	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp