

Project Name

Location Prepared By



SATCO S8530

9WPLH/LED/827/BP/2P

Notes

Status	Active
Watts	9W
Fluorescent Equivalent	18W/26W
Volts	120V-277V
Ballast Type	Туре В
Shape	PL
Base	G24d (2-Pin)
ANSI Base	G24d
Finish	Frost
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	80+
Lumens	900L
Beam Spread	120
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	PL
Operating Position	Horizontal
Technology	LED

Ballasting Requirements Ballast Bypass- Direct wire only 100	0V-277V
Operating Frequency 50/60Hz	
Power Factor 0.99	
Operating Temperature -20C (-4F) to +45C (+113F)	

Physical	
MOL	6.63
MOD	1.09
Housing Color	White
Weight (lb.)	0.14

Additional Information		
Installation Notes	2-pin LED lamps work in both 2-pin (magnetic) and 4-pin (electronic) sockets.	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	

Compliance	
Safety Listing	cULus - Classified; cULus - Certified
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED Lamp