

Project Name

ocation Prepared By



Notes

v] 09-14-2025 23:0

Status	Discontinued
Substitute	S28693
Watts	12W
Incandescent Equivalent	60W
Fluorescent Equivalent	25W
Volts	120V-277V
Ballast Type	Туре В
Shape	_T5
Base	Miniature Bi Pin
ANSI Base	G5
Nominal Length	24
Finish	Frost
CCT (Kelvin)	3500K
Temperature	Neutral White
CRI	80+
Lumens	1400L
Beam Spread	240
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Operating Temperature	-20C (-4F) to +45C (+113F)

Operating Frequency	50/60Hz
Operating Temperature	-20C (-4F) to +45C (+113F)
Physical	
MOL	24
MOD	0.88
Lens Finish	Frost
Housing Color	Silver
Weight (lb.)	0.21

Additional Information	
Shatter-Proof Type	PET Coated
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5-Years

Safety Listing	cULus - Classified; cULus - Certified; ETLus - Sanitation Recognized Component
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp