SATCO NUVO

Project Name

Prepared By



Notes

General	
Status	Discontinued
Substitute	S21267
Watts	4W
Incandescent Equivalent	40W
Volts	120V
Shape	B11
Base	Candelabra
ANSI Base	E12
Finish	Clear
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	350L
Beam Spread	360
Dimmable	Yes-Dimmable
Hours Rated	15000
Product Category	Candle
Technology	LED
Smart Product Info	
IOT Enabled	No
Integrated Camera	No
Electrical	
	60Hz
Electrical Operating Frequency Power Factor	60Hz 0.9
Operating Frequency Power Factor	
Operating Frequency	0.9
Operating Frequency Power Factor Operating Position	0.9 Universal
Operating Frequency Power Factor Operating Position Operating Temperature Physical	0.9 Universal -20C (-4F) to +45C (+113F)
Operating Frequency Power Factor Operating Position Operating Temperature	0.9 Universal
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL	0.9 Universal -20C (-4F) to +45C (+113F)
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus Damp
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus Damp Non-Compliant
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus Damp Non-Compliant Non-Compliant
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years cULus Damp Non-Compliant Non-Compliant Lawful for sale
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status	0.9 Universal -20C (-4F) to +45C (+113F) 3.88 1.38 0.04 Yes 2-Years CULus Damp Non-Compliant Non-Compliant Lawful for sale Lawful for sale

