



Notes

General	
Status	Discontinued
Substitute	S49935R1
Watts	14W
Incandescent Equivalent	100W
Fluorescent Equivalent	25W-32W
Volts	Ballast Dependent
Ballast Type	Туре А
Shape	<u>T8</u>
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss White
CCT (Kelvin)	3500K
Temperature	Neutral White
CRI	80+
Lumens	1800L
Beam Spread	230
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED
Electrical	
Ballasting Requirements	May not be compatible with all rapid start ballasts; Direct Replacement-for use on Instan Startand Rapid Start ballasts with no rewiring required
Operating Temperature	-20C (-4F) to +45C (+113F)
Physical	
MOL	48
MOD	1
Lens Finish	Gloss White
Additional Information	
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years
Compliance	
Сотрпансе	
Safety Listing	cULus
•	cULus Damp
Safety Listing	
Safety Listing Location Rating	Damp
Safety Listing Location Rating DLC Approved	Damp No
Safety Listing Location Rating DLC Approved California Status	Damp No Lawful for sale in California
Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status	Damp  No  Lawful for sale in California  Lawful for sale
Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status	Damp  No  Lawful for sale in California  Lawful for sale  Lawful for sale
Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status	Damp  No  Lawful for sale in California  Lawful for sale  Lawful for sale  Lawful for sale
Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status	Damp  No  Lawful for sale in California  Lawful for sale

FCC Compliant Yes SDS Sheet LED\_Lamp