

Project Name

Prepared By



Notes

General	
Status	Discontinued
Substitute	S49991
Watts	11W
Incandescent Equivalent	60W
Fluorescent Equivalent	25W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	36
Finish	Gloss White
CCT (Kelvin)	3500K
Temperature	Neutral White
CRI	82
Lumens	1450L
Beam Spread	230
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED
Electrical	
Electrical Ballasting Requirements	May not be compatible with all rapid start ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required
	ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring
Ballasting Requirements	ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required
Ballasting Requirements Operating Temperature	ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required
Ballasting Requirements Operating Temperature Physical	ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required -20C (-4F) to +45C (+113F)
Ballasting Requirements Operating Temperature Physical MOL	ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required -20C (-4F) to +45C (+113F)
Ballasting Requirements Operating Temperature Physical MOL MOD	ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required -20C (-4F) to +45C (+113F) 36 1
Ballasting Requirements Operating Temperature Physical MOL MOD Lens Finish	ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required -20C (-4F) to +45C (+113F) 36 1
Ballasting Requirements Operating Temperature Physical MOL MOD Lens Finish Additional Information	ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required -20C (-4F) to +45C (+113F) 36 1 Gloss White
Ballasting Requirements Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes	ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required -20C (-4F) to +45C (+113F) 36 1 Gloss White Not for use in vapor tight fixtures.
Ballasting Requirements Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty	ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required -20C (-4F) to +45C (+113F) 36 1 Gloss White Not for use in vapor tight fixtures.
Ballasting Requirements Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance	ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required -20C (-4F) to +45C (+113F) 36 1 Gloss White Not for use in vapor tight fixtures. 5 Year Limited - T8 LED Bulbs
Ballasting Requirements Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance DLC Approved	ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required -20C (-4F) to +45C (+113F) 36 1 Gloss White Not for use in vapor tight fixtures. 5 Year Limited - T8 LED Bulbs
Ballasting Requirements Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance DLC Approved California Status	ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required -20C (-4F) to +45C (+113F) 36 1 Gloss White Not for use in vapor tight fixtures. 5 Year Limited - T8 LED Bulbs No Lawful for sale in California
Ballasting Requirements Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance DLC Approved California Status Title 20 / 24 Status	ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required -20C (-4F) to +45C (+113F) 36 1 Gloss White Not for use in vapor tight fixtures. 5 Year Limited - T8 LED Bulbs No Lawful for sale in California Lawful for sale
Ballasting Requirements Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance DLC Approved California Status Title 20 / 24 Status Colorado Status	ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required -20C (-4F) to +45C (+113F) 36 1 Gloss White Not for use in vapor tight fixtures. 5 Year Limited - T8 LED Bulbs No Lawful for sale in California Lawful for sale Lawful for sale
Ballasting Requirements Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status	ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required -20C (-4F) to +45C (+113F) 36 1 Gloss White Not for use in vapor tight fixtures. 5 Year Limited - T8 LED Bulbs No Lawful for sale in California Lawful for sale Lawful for sale Lawful for sale
Ballasting Requirements Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Warranty Compliance DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status	ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required -20C (-4F) to +45C (+113F) 36 1 Gloss White Not for use in vapor tight fixtures. 5 Year Limited - T8 LED Bulbs No Lawful for sale in California Lawful for sale

Compliance	
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp