SATCO NUVO

Project Name

ocation Prepared By



SATCO S9497

6.5MR16/LED/40'/35K/12V

Notes

General	
Status	Active
Watts	6.5W
Incandescent Equivalent	50W
Volts	
Shape	MR16
Base	Bi Pin GU5.3
ANSI Base	GU5.3
Finish	Gray
CCT (Kelvin)	3500K
Temperature	Neutral White
CRI	80+
Lumens	500L
Beam Spread	40
Dimmable	Yes-Dimmable
Dimming Note	Check the transformer/driver MFG for dimmer compatibility
Hours Rated	25000
Product Category	MR
Technology	LED
Electrical	
Operating Frequency	60Hz
CBCP	1060
СВСР	1060
CBCP Candlepower	1060 1060
CBCP Candlepower Power Factor	1060 1060 0.93
CBCP Candlepower Power Factor Operating Temperature	1060 1060 0.93
CBCP Candlepower Power Factor Operating Temperature Physical	1060 1060 0.93 -25C (-13F) to +45C (+113F)
CBCP Candlepower Power Factor Operating Temperature Physical MOL	1060 1060 0.93 -25C (-13F) to +45C (+113F)
CBCP Candlepower Power Factor Operating Temperature Physical MOL MOD	1060 1060 0.93 -25C (-13F) to +45C (+113F) 1.772 1.969
CBCP Candlepower Power Factor Operating Temperature Physical MOL MOD Lensed	1060 1060 0.93 -25C (-13F) to +45C (+113F) 1.772 1.969 Lensed Lamp
CBCP Candlepower Power Factor Operating Temperature Physical MOL MOD Lensed Lens Finish	1060 1060 0.93 -25C (-13F) to +45C (+113F) 1.772 1.969 Lensed Lamp Clear
CBCP Candlepower Power Factor Operating Temperature Physical MOL MOD Lensed Lens Finish Housing Color	1060 1060 0.93 -25C (-13F) to +45C (+113F) 1.772 1.969 Lensed Lamp Clear Gray
CBCP Candlepower Power Factor Operating Temperature Physical MOL MOD Lensed Lens Finish Housing Color Weight (lb.)	1060 1060 0.93 -25C (-13F) to +45C (+113F) 1.772 1.969 Lensed Lamp Clear Gray
CBCP Candlepower Power Factor Operating Temperature Physical MOL MOD Lensed Lens Finish Housing Color Weight (lb.) Additional Information	1060 1060 0.93 -25C (-13F) to +45C (+113F) 1.772 1.969 Lensed Lamp Clear Gray 0.08
CBCP Candlepower Power Factor Operating Temperature Physical MOL MOD Lensed Lens Finish Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	1060 1060 0.93 -25C (-13F) to +45C (+113F) 1.772 1.969 Lensed Lamp Clear Gray 0.08
CBCP Candlepower Power Factor Operating Temperature Physical MOL MOD Lensed Lens Finish Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	1060 1060 0.93 -25C (-13F) to +45C (+113F) 1.772 1.969 Lensed Lamp Clear Gray 0.08
CBCP Candlepower Power Factor Operating Temperature Physical MOL MOD Lensed Lens Finish Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	1060 1060 0.93 -25C (-13F) to +45C (+113F) 1.772 1.969 Lensed Lamp Clear Gray 0.08 Yes 5-Years
CBCP Candlepower Power Factor Operating Temperature Physical MOL MOD Lensed Lens Finish Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	1060 1060 0.93 -25C (-13F) to +45C (+113F) 1.772 1.969 Lensed Lamp Clear Gray 0.08 Yes 5-Years
CBCP Candlepower Power Factor Operating Temperature Physical MOL MOD Lensed Lens Finish Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	1060 1060 0.93 -25C (-13F) to +45C (+113F) 1.772 1.969 Lensed Lamp Clear Gray 0.08 Yes 5-Years cULus - Certified; cULus - Listed Damp

Compliance	
Safety Listing	cULus - Certified; cULus - Listed
Location Rating	Damp
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp