SATCO NUVO

Project Name

Prepared By



StatusObsoleteRecessed Can Size4 in.Wattage10.5WVoltage120VFinishBlackCCT (kelvin)2700KColor TemperatureWarm WhiteLumen Output590LIndoor or Outdoor FixtureIndoorSpecificationsEDCRI90+Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensions2.09Width (in.)3.19Height (in.)0.44ComplianceDampENRGY STARNoDLC ApprovedNon-CompliantCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantCalifornia TenperatureYesSpecificationsYesMidth StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantCalifornia StatusNon-CompliantTitle 20 / 24 StatusLeadRothS CompliantYesSpecificationsYesSpecificationsSitesKatditional InformationYesFits 4in. universal cans or retrofitWarranty5-Years	General	
Wattage10.5WVoltage120VFinishBlackCCT (Kelvin)2700KColor TemperatureWarm WhiteLumen Output590LIndoor or Outdoor FixtureIndoorSpecificationsIndoorTechnologyLEDCRI90+Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DinmableYes-DinmableDimensionsUtilityWidth (in.)3.19Height (in.)2.09Weight (lb.)0.44ComplianceDampENERGY STARNoDLC ApprovedNoCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantCalifornia StatusNon-CompliantCalifornia StatusNon-CompliantStores SteetLED_FixtureAdditional InformationYesInstallation NotesFits 4in. universal cans or retrofit	Status	Obsolete
Voltage120VFinishBlackCCT (Kelvin)2700KColor TemperatureWarm WhiteLumen Output590LIndoor or Outdoor FixtureIndoorSpecificationsTechnologyCRI90+Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsWidth (in.)3.19Height (in.)2.09Weight (lb.)0.44ComplianceSafety ListingcETLus - ListedLocation RatingDampENRGY STARNoDLC ApprovedNon-CompliantTitle 20 / 24 StatusNon-CompliantCalifornia StatusNon-CompliantCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesFCC CompliantYesFCC CompliantYesFCC CompliantYesFCA Additional InformationFits 4in. universal cans or retrofit	Recessed Can Size	4 in.
IntegrDiscreteFinishBlackCCT (Kelvin)2700KColor TemperatureWarm WhiteLumen Output590LIndoor or Outdoor FixtureIndoorSpecificationsIndoorTechnologyLEDCRI90+Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsYes-DimmableWidth (in.)3.19Height (in.)0.44Compliance209Safety ListingcETLus - ListedLocation RatingDampENERGY STARNoDLC ApprovedNoCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationFits 4in. universal cans or retrofit	Wattage	10.5W
CCT (Kelvin)2700KColor TemperatureWarm WhiteLumen Output590LIndoor or Outdoor FixtureIndoorSpecificationsLEDTechnologyLEDCRI90+Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensions2.09Width (in.)3.19Height (in.)0.44Compliance2Safety ListingcETLus - ListedLocation RatingDampENERGY STARNoDLC ApprovedNon-CompliantTitle 20 / 24 StatusNon-CompliantCalifornia StatusNon-CompliantTitle 20 / 24 StatusKon-CompliantYesYesSDS SheetLED_FixtureAdditional InformationFits 4in. universal cans or retrofit	Voltage	120V
Color TemperatureWarm WhiteLumen Output590LIndoor or Outdoor FixtureIndoorSpecificationsIteDTechnologyLEDCRI90+Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsUtility (in.)Width (in.)3.19Height (in.)2.09Weight (lb.)0.44ComplianceSafety ListingSafety ListingcETLus - ListedLocation RatingDampENERGY STARNoDLC ApprovedNoCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationFits 4in. universal cans or retrofit	Finish	Black
Lumen Output590LIndoor or Outdoor FixtureIndoorSpecificationsIndoorTechnologyLEDCRI90+Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsVidth (in.)Width (in.)3.19Height (in.)2.09Weight (lb.)0.44ComplianceSafety ListingSafety ListingcETLus - ListedLocation RatingDampENERGY STARNoDLC ApprovedNon-CompliantCalifornia StatusNon-CompliantCalifornia StatusNon-CompliantCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationFits 4in. universal cans or retrofit	CCT (Kelvin)	2700K
Indoor or Outdoor FixtureIndoorSpecificationsIndoorTechnologyLEDCRI90+Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsYes-DimmableWidth (in.)3.19Height (in.)0.44ComplianceSafety ListingcETLus - ListedLocation RatingDampENERGY STARNoDLC ApprovedNoCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantCompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationFits 4in. universal cans or retrofit	Color Temperature	Warm White
SpecificationsTechnologyLEDCRI90+Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsYes-DimmableWidth (in.)3.19Height (in.)2.09Weight (lb.)0.44ComplianceSafety ListingcETLus - ListedLocation RatingDampENERGY STARNoDLC ApprovedNoCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantCompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationFits 4in. universal cans or retrofit	Lumen Output	590L
TechnologyLEDTechnologyLEDCRI90+Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsWidth (in.)3.19Height (in.)2.09Weight (lb.)0.44ComplianceSafety ListingcETLus - ListedLocation RatingDampENERGY STARNoDLC ApprovedNon-CompliantTitle 20 / 24 StatusNon-CompliantCalifornia StatusNon-CompliantCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationInstallation NotesFits 4in. universal cans or retrofit	Indoor or Outdoor Fixture	Indoor
CRI90+Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensions2.09Width (in.)3.19Height (in.)2.09Weight (lb.)0.44ComplianceSafety ListingcETLus - ListedLocation RatingDampENERGY STARNoDLC ApprovedNoCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantCalifornia Prop 65LeadRoHS CompliantYesSDS SheetLED_FixtureAdditional InformationFits 4in. universal cans or retrofit	Specifications	
Rated Hours50000Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensionsYes-DimmableWidth (in.)3.19Height (in.)2.09Weight (lb.)0.44ComplianceSafety ListingcETLus - ListedLocation RatingDampENERGY STARNoDLC ApprovedNoCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationFits 4in. universal cans or retrofit	Technology	LED
Operating Temperature-20C (-4F) to +45C (+113F)DimmableYes-DimmableDimensions3.19Width (in.)3.19Height (in.)2.09Weight (lb.)0.44ComplianceSafety ListingcETLus - ListedLocation RatingDampENERGY STARNoDLC ApprovedNoCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantCalifornia Prop 65LeadRCMS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationFits 4in. universal cans or retrofit	CRI	90+
DimmableYes-DimmableDimensionsWidth (in.)3.19Height (in.)2.09Weight (lb.)0.44ComplianceSafety ListingcETLus - ListedLocation RatingDampENERGY STARNoDLC ApprovedNoCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantCalifornia Prop 65LeadROHS CompliantYesSDS SheetLED_FixtureAdditional InformationFits 4in. universal cans or retrofit	Rated Hours	50000
DimensionsWidth (in.)3.19Height (in.)2.09Weight (lb.)0.44ComplianceSafety ListingcETLus - ListedLocation RatingDampENERGY STARNoDLC ApprovedNoCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationInstallation NotesFits 4in. universal cans or retrofit	Operating Temperature	-20C (-4F) to +45C (+113F)
Width (in.)3.19Height (in.)2.09Weight (lb.)0.44ComplianceSafety ListingcETLus - ListedLocation RatingDampENERGY STARNoDLC ApprovedNoCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationInstallation NotesFits 4in. universal cans or retrofit	Dimmable	Yes-Dimmable
Height (in.)2.09Weight (lb.)0.44ComplianceSafety ListingcETLus - ListedLocation RatingDampENERGY STARNoDLC ApprovedNoCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationFits 4in. universal cans or retrofit	Dimensions	
Weight (Ib.)0.44ComplianceSafety ListingcETLus - ListedLocation RatingDampENERGY STARNoDLC ApprovedNoCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationFits 4in. universal cans or retrofit	Width (in.)	3.19
ComplianceSafety ListingcETLus - ListedLocation RatingDampENERGY STARNoDLC ApprovedNoCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationInstallation NotesFits 4in. universal cans or retrofit	Height (in.)	2.09
Safety ListingcETLus - ListedLocation RatingDampENERGY STARNoDLC ApprovedNoCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_FixtureAdditional InformationInstallation NotesFits 4in. universal cans or retrofit	Weight (lb.)	0.44
Location Rating Damp ENERGY STAR No DLC Approved No California Status Non-Compliant Title 20 / 24 Status Non-Compliant California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Fits 4in. universal cans or retrofit	Compliance	
ENERGY STAR No DLC Approved No California Status Non-Compliant Title 20 / 24 Status Non-Compliant California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Fits 4in. universal cans or retrofit	Safety Listing	cETLus - Listed
DLC Approved No California Status Non-Compliant Title 20 / 24 Status Non-Compliant California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Fits 4in. universal cans or retrofit	Location Rating	Damp
California Status Non-Compliant Title 20 / 24 Status Non-Compliant California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Fits 4in. universal cans or retrofit	ENERGY STAR	No
Title 20 / 24 Status Non-Compliant California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Fits 4in. universal cans or retrofit	DLC Approved	No
California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Fits 4in. universal cans or retrofit	California Status	Non-Compliant
RoHS Compliant Yes FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Installation Notes Fits 4in. universal cans or retrofit	Title 20 / 24 Status	Non-Compliant
FCC Compliant Yes SDS Sheet LED_Fixture Additional Information Installation Notes Fits 4in. universal cans or retrofit	California Prop 65	Lead
SDS Sheet LED_Fixture Additional Information Installation Notes Fits 4in. universal cans or retrofit	RoHS Compliant	Yes
Additional Information Installation Notes Fits 4in. universal cans or retrofit	FCC Compliant	Yes
Installation Notes Fits 4in. universal cans or retrofit	SDS Sheet	LED_Fixture
	Additional Information	
Warranty 5-Years	Installation Notes	Fits 4in. universal cans or retrofit
	Warranty	5-Years

SATCO S9500 10.5WLED/4-BASE/27K/540L/120V

Notes

