## SATCO NUVO

Project Name

Location

Prepared By



## **SATCO S9677**

120W/LED/HID/40K/100-277V EX39

Notes

3 05 15 000 10 10 5

General	
General	
Status	Discontinued
Substitute	S49677
Watts	120W
Incandescent Equivalent	750W
Fluorescent Equivalent	200W
HID Equivalent	600W
Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	15600L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Corncob
Technology	LED
Min Compartment Size	Length: 17.3 in. Width: 9.25 in. Depth: 9.25 in.
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	
Mading Vallage	AC 00 005V
Working Voltage	AC 90-305V
On a ration Francisco	E0/0011-
Operating Frequency	50/60Hz
Power Factor	0.96
Power Factor Operating Position	0.96 Universal
Power Factor Operating Position Surge Protection	0.96 Universal Built-in surge protection
Power Factor Operating Position	0.96 Universal
Power Factor Operating Position Surge Protection	0.96 Universal Built-in surge protection
Power Factor Operating Position Surge Protection Operating Temperature	0.96 Universal Built-in surge protection
Power Factor Operating Position Surge Protection Operating Temperature Physical	0.96 Universal Built-in surge protection -20C (-4F) to +65C (+149F)
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL	0.96 Universal Built-in surge protection -20C (-4F) to +65C (+149F)
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD	0.96 Universal Built-in surge protection -20C (-4F) to +65C (+149F)
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish	0.96 Universal Built-in surge protection -20C (-4F) to +65C (+149F)  10.38 5.88 Clear
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color	0.96 Universal Built-in surge protection -20C (-4F) to +65C (+149F)  10.38 5.88 Clear
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Housing Color Additional Information	0.96 Universal Built-in surge protection -20C (-4F) to +65C (+149F)  10.38 5.88 Clear White
Power Factor Operating Position Surge Protection Operating Temperature  Physical  MOL  MOD Lens Finish Housing Color  Additional Information Includes	0.96 Universal Built-in surge protection -20C (-4F) to +65C (+149F)  10.38 5.88 Clear White Safety chain
Power Factor Operating Position Surge Protection Operating Temperature  Physical MOL MOD Lens Finish Housing Color  Additional Information Includes Rated For Enclosed Fixture	0.96 Universal Built-in surge protection -20C (-4F) to +65C (+149F)  10.38 5.88 Clear White  Safety chain Yes IP65
Power Factor Operating Position Surge Protection Operating Temperature  Physical  MOL  MOD  Lens Finish Housing Color  Additional Information Includes Rated For Enclosed Fixture IP Rating	0.96 Universal Built-in surge protection -20C (-4F) to +65C (+149F)  10.38 5.88 Clear White  Safety chain Yes
Power Factor Operating Position Surge Protection Operating Temperature  Physical  MOL  MOD  Lens Finish Housing Color  Additional Information  Includes  Rated For Enclosed Fixture IP Rating Installation Notes	0.96 Universal Built-in surge protection -20C (-4F) to +65C (+149F)  10.38 5.88 Clear White  Safety chain Yes IP65 Not for use in vapor tight fixtures.
Power Factor Operating Position Surge Protection Operating Temperature  Physical  MOL  MOD  Lens Finish Housing Color  Additional Information Includes Rated For Enclosed Fixture IP Rating Installation Notes Warranty	0.96 Universal Built-in surge protection -20C (-4F) to +65C (+149F)  10.38 5.88 Clear White  Safety chain Yes IP65 Not for use in vapor tight fixtures.
Power Factor Operating Position Surge Protection Operating Temperature  Physical  MOL  MOD  Lens Finish Housing Color  Additional Information  Includes Rated For Enclosed Fixture IP Rating Installation Notes Warranty  Compliance  Safety Listing	0.96 Universal Built-in surge protection -20C (-4F) to +65C (+149F)  10.38 5.88 Clear White  Safety chain Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro  CULus - Classified; cULus - Certified
Power Factor Operating Position Surge Protection Operating Temperature  Physical  MOL  MOD Lens Finish Housing Color  Additional Information Includes Rated For Enclosed Fixture IP Rating Installation Notes Warranty  Compliance  Safety Listing Location Rating	0.96 Universal Built-in surge protection -20C (-4F) to +65C (+149F)  10.38 5.88 Clear White  Safety chain Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro
Power Factor Operating Position Surge Protection Operating Temperature  Physical  MOL  MOD Lens Finish Housing Color  Additional Information Includes Rated For Enclosed Fixture IP Rating Installation Notes Warranty  Compliance  Safety Listing Location Rating Energy Star	0.96 Universal Built-in surge protection -20C (-4F) to +65C (+149F)  10.38 5.88 Clear White  Safety chain Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro  cULus - Classified; cULus - Certified Damp
Power Factor Operating Position Surge Protection Operating Temperature  Physical  MOL  MOD Lens Finish Housing Color  Additional Information Includes Rated For Enclosed Fixture IP Rating Installation Notes Warranty  Compliance  Safety Listing Location Rating	0.96 Universal Built-in surge protection -20C (-4F) to +65C (+149F)  10.38 5.88 Clear White  Safety chain Yes IP65 Not for use in vapor tight fixtures. 5 Year Limited - Hi-Pro  cULus - Classified; cULus - Certified Damp No

California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: <a href="https://www.satco.com/">https://www.satco.com/</a>



