

Notes

vw] 09-09-2025 21:5

Additional Info

Shatter-Proof Type

Installation Notes

Specification Note

General	
Status	Discontinued
Watts	24W
Incandescent Equivalent	100W
Fluorescent Equivalent	54W/59W
Volts	120V-277V
Shape	T8
Base	Single Pin
ANSI Base	Fa8
Nominal Length	96
Finish	Gloss White
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	3500L
Beam Spread	230
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED
Electrical	
Ballasting Requirements	May not be compatible with all instant start ballasts; Direct Replacement-for use on electronic Instant Start ballasts with no rewiring required
Operating Temperature	-20C (-4F) to +45C (+113F)
Physical	
MOL	96
MOD	1
Material	Glass
Lens Finish	Gloss White

Warranty	5-Years
Compliance	
Safety Listing	cULus - Listed
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED Lamp

Note: Must be ordered in full case quantities

Not for use in vapor tight fixtures.

120 or 277 volt; Shatterproof coated