

Project Name

Location

Prepared By



## SATCO S9711-TF

25T5/LED/46-850/DR/TF SHATTER

### Notes

(www) 09-11-2023 23:43:02

### General

Status	Discontinued
Watts	25W
Incandescent Equivalent	100W
Fluorescent Equivalent	54W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	T5
Base	Miniature Bi Pin
ANSI Base	G5
Nominal Length	48
Finish	Gloss White
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	3200L
Beam Spread	185
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

### Electrical

Ballasting Requirements	Ballast required; Direct Replacement-for use on Electronic Instant Start and Rapid Start ballasts with no rewiring required; May not be compatible with all rapid start ballasts
Operating Temperature	-20C (-4F) to +45C (+113F)

### Physical

MOL	48
MOD	0.63
Lens Finish	Gloss White

### Additional Information

Shatter-Proof Type	Yes
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5-Years

### Compliance

Safety Listing	cULus - Classified
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp