

Project Name

Location

Prepared By



# SATCO S9718

25T5/LED/46-840/BP/277V

**Notes**

[www] 05-15-2024 04:42:59

**General**

Status	Discontinued
Substitute	S39718
Watts	25W
Incandescent Equivalent	100W
Fluorescent Equivalent	54W
Volts	277V
Ballast Type	Type A
Shape	T5
Base	Miniature Bi Pin
ANSI Base	G5
Nominal Length	48
Finish	Frost
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	83
Lumens	3300L
Beam Spread	230
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

**Electrical**

Ballasting Requirements	May not be compatible with all rapid start ballasts; Direct Replacement-for use on Instant Startand Rapid Start ballasts with no rewiring required
Power Factor	0.95
Operating Temperature	-20C (-4F) to +45C (+113F)

**Physical**

MOL	48
MOD	0.63
Lens Finish	Frost

**Additional Information**

Shatter-Proof Type	Yes
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5 Year Limited - T5 LED Bulbs

**Compliance**

Safety Listing	cULus - Classified; cULus - Certified
Location Rating	Damp
Energy Star	No
DLC Approved	No
CA T20 / T24 Rationale	Exempt - Shatter Proof
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale

Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc.  
All Rights Reserved

For More Information Visit:  
<https://www.satco.com/>

